

What Varilight dimmer do I need?



V-Dim is best suited for Incandescent GLS filament lamps on 1 or 2 Way circuits. It is available as a 1-4 gang dimmer, as a replacement module, or in a grid format.
NOT SUITABLE FOR LED LOADS



V-Plus dimmers are leading-edge and best suited for halogen lamps (including eco-halogen and low-voltage dichroic) and all types of electronic and wire wound low voltage transformers. **NOT SUITABLE FOR LED LOADS**



Same dimming technology as our V-Plus dimmers, but in a remote control/touch dimming format. The dimmer has a round touch button which has an IR sensor in the centre. These dimmers are one way only. **NOT SUITABLE FOR LED LOADS** (Please note: These cannot be used with a standard 2 way switch)



V-Com is suitable for 1-10 LED lamps (Max load 100w) per gang. Available as a 1-4 gang dimmer in all finishes, as a replacement module, or in grid format.



V-Pro is suitable if you have a LED load that is more than 10 lamps or 100w. They are suitable for up to 30 LED lamps (Max load 300w) per gang. They are available as a 1-3 gang dimmer and as a replacement dimmer module.



Features the same dimming technology as our V-Pro LED dimmers, but in a remote control/touch dimming format. The V-Pro IR is suitable for up to 10 LED (max load of 100w). The dimmer has a round touch button which has an IR sensor in the centre. The master dimmers are one way unless used with a V-Pro IR Slave.
(Please note: These cannot be used with a standard 2 way switch)



The Eclique2 dimmer switches are remote control dimmers, but unlike the V-Pro IR these feature a rectangular switch which operates in similar way to a standard rocker switch. Available as a finished product or in a grid format. The master dimmers are one way unless used with an Eclique2 Slave. (Please note: These cannot be used with a standard 2 way switch)

<i>Dimmer Type</i>	<i>Suitable For</i>	<i>Notes</i>	<i>Page Number</i>
	<i>Mains GLS</i>	<i>Incandescent GLS filament lamps – NOT SUITABLE FOR LED</i>	<i>76-77</i>
	<i>Halogen</i>	NOT SUITABLE FOR LED	<i>78</i>
	<i>Halogen</i>	<i>Round Button 1 Way only NOT SUITABLE FOR LED</i>	<i>75</i>
	<i>LED loads up to 10 lamps (Max 100W) per gang</i>	<i>VL JQP401W has been superseded by KQP101W JP400MOD has been superseded by MKP100</i>	<i>79</i>
	<i>LED loads up to 30 lamps (Max 300W) per gang including LED Panels</i>	<i>Available as a plated product 1-3 gang or as a replacement module MJP300</i>	<i>80</i>
	<i>LED loads up to 10 lamps (Max 100W) per gang</i>	Round Button <i>Remote Dimmer Suitable for LED or Halogen loads 1 Way or 2 Way when used with a slave.</i>	<i>74</i>
	<i>LED loads up to 10 lamps (Max 100W) per gang</i>	Rectangular Button <i>Remote/Touch Dimmer Suitable for LED or Halogen loads 1 Way or 2 Way when used with a slave.</i>	<i>Page 75 or tlc-direct.co.uk for full range</i>

Please contact our sales office on 01293 851563 if you have any queries regarding dimming or need any help with product codes.

