



Features

- Presence or Absence detection designed for the automatic control of lighting installations
- Optional IR remote control for remote set-up and adjustment (sold separately)
- Option for manual push button operation
- Multi sensor parallel wiring capability
- Up to 600W LED load for commercial lighting installation
- Discreet flat PIR lens technology
- Adjustable time delay and lux settings with sensitivity control via remote control

Dimensions

	Height (mm)	Width (mm)	Depth (mm)	Weight (g)
PDSM361AB	105	105	48	125
PDSM361ABBLK	105	105	48	125

Line Diagram(s)



Single Channel 360° Ceiling PIR Presence/Absence Detector – Surface Mount

Range

PDSM361AB	Single Channel 360° Ceiling PIR Presence/Absence Detector – Surface Mount
PDSM361ABBLK	Single Channel 360° Ceiling PIR Presence/Absence Detector – Surface Mount (Black)

Technical Specification

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface Mount
Earth Class Rating	Class II
Operating Temperature	-20°C to 40°C
Ingress Protection Rating	IP54
Setting Type	Dial
Approved Mounting Height (m)	2.5 - 4m
Presence Detection (m)	4 Diameter
Motion Detection (m)	8m Diameter at 2.5m
	Diameter Mounting Height, 10m at 4m Mounting Height
Detection Angle	360°
Mounting Hole Centres (mm)	50.8, 60, 70, 80
Standby Consumption	<0.5W
Number Of Channels	1
Switch Rating	800VA/600W LED, 2200W Incandescent, 2200W Halogen, 1200VA/140uF Fluorescent
ON Time Adjustment	30 Seconds to 30 Minutes. User Adjustable
LUX Level	10 to 2000
Detection Range (m)	8m Diameter at 2.5m
	Mounting Height, 10m at 4m Diameter Mounting Height
Permanent ON Facility	Yes (IR10AB Remote Required)
Dusk Till Dawn	No
Multiple Unit Support	Up to 8 Units in Parallel
Cable Entry(s)	Back Entry
Body Construction	Polycarbonate
Product Colour	Black, White
Accessories (Included)	Surface Box
Accessories (Optional)	IR10AB (Remote Control)