
Data sheet


ZV210N – Automatic Light Switch With Photocell - 2 Wire



Product Image & Line Diagram







Technical Data

General	
Operating Voltage	230v AC
Frequency	50Hz
Battery	9V DC replaceable battery (Supplied)
Connection	2 wire
Installation Type	Surface/Recessed
Class Rating	Class II
Mounting Height	1.1m for optimum detection range
Minimum Depth of Wall-box	25mm
Switch Type	Single or Two way
Switch Rating	2000W Incandescent/Halogen, 250W Fluorescent (Low-loss
-	or Electronic Ballast), 250W CFL (Low- loss or Electronic
	Ballast), 400W LED Lighting (PF 0.9 or higher)
Operating Temperature	-0°C - 40°C
Dimensions	Height 86mm, Width 86mm, Depth 29.5mm
Weight	104g
EAN	5012483015032
Designed In Accordance To	BS EN 60730-2-7 Includes updates and amendments.
Guarantee Period	3 Years
Functions	
On-time Adjustment	0, 2, 4, 6, 8 hours or D (Dusk until Dawn)
Override	Manual ON/OFF switch
Lux Adjustment	1~10 lux (Moon symbol) to 300 lux (Sun symbol)
Red LED Window	Will light solid red to indicate that an On-Time duration is set
Low Battery Indication	The LED will pulse 1 sec ON, 8 secs OFF
Construction	
Casing	Polycarbonate



A **theben** Group Company Article Number: ZV210N DS240519

