



GB



General purpose floodlight that features a high impact anticorrosive polycarbonate lens and body. Integral control gear and also available complete with lamp which makes this floodlight speedy and simple to install. Standard body colours are Black, White or Silver Grey. Suitable for all types of applications and weather conditions. For dusk to dawn operation photocell versions are available for all types.



- S.1 - SON-E Δ (E27) Internal ignitor
- H.1 - Metal Halide (RX7s)
- H.3 - Metal Halide (E27)
- CF.4 - Compact fluorescent, 2 pin, (GX24d-3) 26W - triple
- CF.5 - Compact fluorescent, 4 pin, (GX24d-4) 32W - triple



DESCRIPTION	LAMP	Wt.(kg)	PART No.	WHITE	SILVER
SYMMETRIC REFLECTOR POLYCARBONATE IP65					
HIGH PRESSURE SODIUM Δ					
70W - BLACK	S.1	3.90	GB70S	/W	/S
METAL HALIDE					
70W - BLACK	H.1	3.90	GB70H	/W	/S
100W - BLACK E27	H.3	3.90	GB100H	/W	/S
COMPACT FLUORESCENT					
26W - BLACK	CF.4	3.90	GB26	/W	/S
32W - BLACK	CF.5	3.90	GB32	/W	/S



PC PHOTOCELL OPTIONS ARE AVAILABLE ON ALL TYPES, TO ORDER SUFFIX CODE WITH /PC. e.g. GB70S/PC

TECHNICAL SPECIFICATION

- HOUSING & FRAME Thermo-plastic polycarbonate
- DIFFUSERS Polycarbonate
- PHOTOCELL Photocell available for all types
- REFLECTORS Anodised polished aluminium
- CONTROL GEAR Available with a wide variety of options
- SUPPLY ACCESS Hinged front cover opening
- COLOURS Black RAL 9011, Silver RAL 7000, White RAL 9003

WINDAGE SCX=0.11M2

