

# Floor Boxes

## Easy to fit - Easy to handle


### UNIFFB3L-90, Access Floor Box; 3 Compartment Cavity Floor Box



#### Specifications

- Floor box manufactured from galvanised steel
- 25 & 20mm knockouts to accept flexible conduit
- Frame and lid moulded from high impact polycarbonate
- Galvanised lid insert for strength
- Easy grip recessed lifting handle
- Compact design: 305x220mm floor cut-out
- Clamp fixing for fast installation
- Large range of accessory plates
- Special plates available to order
- Clean earthed sockets available


#### Top Clearance Height




#### Accessory Plates




**FOBP300**  
Blank Plate




**FOBP307**  
RJ45/LJ6C Plate




**FOBP303**  
Standard Twin  
Accessory Plate




**FOBP309**  
Alpha Snap Plate




**FOBP305**  
Twin Switched Sockets



**FOBP310**  
Double LJU3/4/5 Plate



**FOBP306**  
6x RJ45/LJ6C Data Plate



**FOBP312**  
2 Euro Standard  
50x50mm Plate

#### Dimensions

- Floor Cut Out: 305x220mm
- Floor Box Depth: 90mm
- Plug Top Clearance: 40mm
- Overall Frame & Lid: 315x231mm
- Frame Lid Recess: 6.5mm
- Accessories Plates: 185x89mm

**UNIVOLT (UK) LTD**  
 Unit 4, Quadrant Park  
 Black Fan Road  
 Welwyn Garden City AL7 1FS  
 England

Tel.: 01707 379 820

Fax: 01707 379 821

sales@univolt.co.uk

www.univolt.co.uk