

## **Data Sheet**

Product Code: YT150Z



Product Description: 0-150VA Dimmable Low Voltage Lighting Transformer (with Terminals)

Product Category: Electronic Transformer

Barcode: 5021575960051

Dimensions: 167x52.5x38.5mm

Net Weight: 210g Gross Weight: 212g Fixing Centres: N/A

Depth from Mounting Face:

Recommended Back Box Depth: N/A

Operating Voltage: 230v 50Hz

Maximum Load Rating: 150W

 $\label{eq:maximum Current Rating: 230V AC: 0.65A / 11.5V AC 13.0A} % Terminal (Live) Diameter: 2.6mm; Capacity: 2 x 1.5mm^2 % Terminal (Neutral) Diameter: 2.6mm; Capacity: 2 x 1.5mm^2 % Terminal (Neutral) Diameter: 2.6mm; Capacity: 2 x 1.5mm^2 % Terminal (Neutral) Diameter: 2.6mm; Capacity: 2 x 1.5mm^2 % Terminal (Neutral) Diameter: 2.6mm; Capacity: 2 x 1.5mm^2 % Terminal (Neutral) Diameter: 2.6mm; Capacity: 2 x 1.5mm^2 % Terminal (Neutral) Diameter: 2.6mm; Capacity: 2 x 1.5mm^2 % Terminal (Neutral) Diameter: 2.6mm; Capacity: 2 x 1.5mm^2 % Terminal (Neutral) Diameter: 2.6mm; Capacity: 2 x 1.5mm^2 % Terminal (Neutral) Diameter: 2.6mm; Capacity: 2 x 1.5mm^2 % Terminal (Neutral) Diameter: 2.6mm; Capacity: 2 x 1.5mm^2 % Terminal (Neutral) Diameter: 2.6mm; Capacity: 2 x 1.5mm^2 % Terminal (Neutral) Diameter: 2.6mm; Capacity: 2 x 1.5mm^2 % Terminal (Neutral) Diameter: 2.6mm; Capacity: 2 x 1.5mm^2 % Terminal (Neutral) Diameter: 2.6mm; Capacity: 2 x 1.5mm^2 % Terminal (Neutral) Diameter: 2.6mm; Capacity: 2 x 1.5mm^2 % Terminal (Neutral) Diameter: 2.6mm; Capacity: 2 x 1.5mm^2 % Terminal (Neutral) Diameter: 2.6mm; Capacity: 2 x 1.5mm^2 % Terminal (Neutral) Diameter: 2.6mm % Terminal ($ 

Intended Applications: Indoor Use Only. Domestic lighting circuits.

Safety Advice: Minimum distance between transformer and lamp: 30cm. This product is not suitable for use with LEDs.. Maximum distance between transformer and lamp: 2m.

**Applicable Safety Standard:** EN 61347-1, EN 61347-2-2, EN 61547, EN 55015 & EN 61000-3-2

Commodity Code: 85043180

Declaration of Conformity

Product Features

 $\ensuremath{\boldsymbol{\Theta}}$  Soft start gently brings lights up to full brightness when you switch on and extends lamp life

Auto-resetting overload protection and over-temperature

② 2 x pairs of input terminals and 3 x pairs of output terminals

**⊘** Short circuit protection - IP20

O No minimum rating



MADE IN THE EU

All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to identify latest version.

Date of Issue: 06th February 2022 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.