



Data Sheet

Product Code: HK4LO

This product is no longer available for purchase

Product Description: 2-Gang 2-Way Push-On/Off Rotary Dimmer 2 x

40-250W

Range: Kilnwood
Finish: Limed Oak

Product Category: V-Dim Dimmer

Insert/Knob Colour: Limed Oak Knobs

Barcode: 5021575970210

Dimensions: 96x96x52mm

Faceplate Depth: 15mm

Net Weight: 156g Gross Weight: 158g Fixing Centres: 60.3mm

Depth from Mounting Face:

Recommended Back Box Depth: 25mm

Operating Voltage: 230v 50Hz

Maximum Load Rating: Halogen; 250W

Maximum Current Rating: 1.1A

Terminal (Live) Diameter: 3.2mm; Capacity: 3 x 1.5mm²
Terminal (Earth) Diameter: 3.3mm; Capacity: 3 x 1.5mm²

Intended Applications: Indoor Use Only. Domestic lighting circuits.

Safety Advice: Not suitable for wire-wound low voltage transformers, fluorescent lighting, motors or fans. Do not overload. Product Must

Be Earthed.

Applicable Safety Standard: BS 5518

Commodity Code:



Product Features

⊘ V-Dim dimming technology

❷ Ideal for incandescent lighting including mains and low voltage halogen

High grade sustainable timber



10 YEAR GUARANTEE



Declaration of Conformity

All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to identify latest version.

Date of Issue: 06th February 2022 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.