



Data Sheet Product Code: HT3

This product can also be made using our Matrix System, using the products WT1 + MTP402 x 1

**Product Description:** 1-Gang 2-Way Push-On/Off Rotary Dimmer 1 x 60-400W

Range: Classic

Finish: Brushed Steel

Product Category: V-Dim Dimmer

Insert/Knob Colour: Steel Knob

Barcode: 5021575031591

Dimensions: 91x91x46mm

Faceplate Depth: 8mm

Net Weight: 146g

Gross Weight: 148g

Fixing Centres: 60.3mm

Depth from Mounting Face: 17.5mm

Recommended Back Box Depth: 25mm

Operating Voltage: 230v 50Hz

Maximum Load Rating: Halogen; 400W

Maximum Current Rating: 1.7A

Terminal (Live) Diameter: 3.2mm; Capacity: 3 x 1.5mm<sup>2</sup>

Terminal (Earth) Diameter: 3.3mm; Capacity: 3 x 1.5mm<sup>2</sup>

Intended Applications: Indoor Use Only. Domestic lighting circuits.

**Safety Advice:** Not suitable for wire-wound low voltage transformers, fluorescent lighting, motors or fans. Do not overload. Product Must



## Product Features

⊘ V-Dim dimming technology

❷ Ideal for incandescent lighting including mains and low voltage halogen

O Bevelled edge faceplate



**10 YEAR GUARANTEE** 



Applicable Safety Standard: BS 5518

Be Earthed.

## Declaration of Conformity

All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to identify latest version.

Date of Issue: 06th February 2022 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.