



Data Sheet Product Code: IJDLS003S



Product Features

⊘ V-Pro intelligent dimming technology

O Use with touch & remote V-Pro IR master dimmers in multi-way circuits

- Ø Soft start feature and intelligent overload protection
- Ø Sleek, low-profile screwless faceplate



10 YEAR GUARANTEE



Product Description: 3-Gang Tactile Touch Control Dimming Supplementary Controller for use with Master on 2-Way Circuits (Twin Plate)

Range: Screwless

Finish: Premium Black

Product Category: V-Pro IR Dimmer

Insert/Knob Colour: Chrome Buttons

Barcode: 5021575057096

Dimensions: 86x147x30mm

Faceplate Depth: 4mm

Net Weight: 169g

Gross Weight: 172g

Fixing Centres: 120.6mm

Depth from Mounting Face: 24.2mm

Recommended Back Box Depth: 35mm

Operating Voltage: 230v 50Hz

Maximum Load Rating: Refer to Master Dimmer

Maximum Current Rating: Refer to Master Dimmer

Terminal (Live) Diameter: 3.2mm; Capacity: 3 x 1.5mm²

Terminal (Earth) Diameter: 3.3mm; Capacity: 3 x 1.5mm²

Intended Applications: Indoor Use Only. Domestic lighting circuits including many dimmable LEDs.

Note: Some LED lamps are not designed for electronic dimmer switches and may remain illuminated even when a dimmer switch is turned off. This can be corrected using one Varilight LEDFix load regulator per circuit (part number YAGF-P). **Safety Advice:** Not suitable for use with non-dimmable fluorescent bulbs and tubes, wire-wound or toroidal transformers, TRIAC dimmable loads or electric motors. Do not overload. Product Must Be Earthed.

Applicable Safety Standard: BS EN 60669-2-1

Commodity Code: 85365005

Declaration of Conformity

All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to identify latest version.

Date of Issue: 06th February 2022 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.