



Data Sheet Product Code: JCE103



Product Features

remote)

V-Pro intelligent dimming technology

Supplementary Controller unit(s)

Bevelled edge faceplate

O Tactile touch control or remote control from dedicated handset or spare button on an existing handset (e.g. TV

Ø Soft start feature and intelligent overload protection

Product Description: 3-Gang 1-Way V-Pro Multi-Point Remote/Tactile Touch Control Master LED Dimmer 3 x 0-100W (1-10 LEDs) (Twin Plate)

Range: Classic

Finish: Mirror Chrome

Product Category: V-Pro Multi-Point Remote (formerly Eclique2) Dimmer

Insert/Knob Colour: Chrome Buttons

Barcode: 5021575532166

Dimensions: 91x150x27mm

Faceplate Depth: 8mm

Net Weight: 199g

Gross Weight: 202g

Fixing Centres: 120.6mm

Depth from Mounting Face: 16.1mm

Recommended Back Box Depth: 25mm

Operating Voltage: 230v 50Hz

Maximum Load Rating: LED; 100W (Max. 10 lamps)

Maximum Current Rating: 1.1A

Terminal (Live) Diameter: 3.2mm; Capacity: 3 x 1.5mm²

Terminal (Earth) Diameter: 3.3mm; Capacity: 3 x 1.5mm²



Intended Applications: Indoor Use Only. Domestic lighting circuits including many dimmable LEDs.

Note: Some LED lamps are not designed for electronic dimmer switches and may remain illuminated even when a dimmer switch is turned off. This can be corrected using one Varilight LEDFix load regulator per circuit (part number YAGF-P).

10 YEAR GUARANTEE

Safety Advice: Not suitable for use with non-dimmable fluorescent bulbs and tubes, wire-wound or toroidal transformers, TRIAC dimmable loads or electric motors. Do not overload. Product Must Be Earthed.

Applicable Safety Standard: BS EN 60669-2-1

Commodity Code: 85365005

Declaration of Conformity

All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to identify latest version.

Date of Issue: 06th February 2022 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.