



## **Data Sheet**

Product Code: JDYP252S.AC

Product Description: 2-Gang 2-Way Push-On/Off Rotary LED

Dimmer 2 x 0-120W (1-10 LEDs)

Range: Screwless

Finish: Cu29 Raw Copper

Product Category: V-Pro Dimmer

Insert/Knob Colour: Cu29 Raw Copper Knobs

Barcode: 5021575999846

Dimensions: 86x86x48mm

Faceplate Depth: 4mm

Net Weight: 216g

Gross Weight: 218g

Fixing Centres: 60.3mm

Depth from Mounting Face: 23.6mm

Recommended Back Box Depth: 35mm

Operating Voltage: 230v 50Hz

Maximum Load Rating: LED; 120W (Max. 10 lamps)

Maximum Current Rating: 0.9A

Terminal (Live) Diameter: 3.2 mm; Capacity:  $3 \times 1.5 mm^2$ 

Terminal (Earth) Diameter: 3.3mm; Capacity: 3 x 1.5mm<sup>2</sup>

**Intended Applications:** Indoor Use Only. Domestic lighting circuits including many dimmable LEDs.

Safety Advice: Not suitable for use with non-dimmable fluorescent bulbs and tubes, wire-wound or toroidal transformers, TRIAC dimmable loads or electric motors. Do not overload. Product Must Be

Earthed.

Applicable Safety Standard: BS EN 60669-2-1

Commodity Code: 85365005



## **Product Features**

**⊘** V-Pro intelligent dimming technology

**⊘** Soft start feature and intelligent overload protection

 Adjustable minimum brightness setting and choice of driving modes

**②** Works alongside routine cleaning and sanitisation procedures to reduce the spread of infection. To remain effective the surface must not be coated in any way. Without regular cleaning this product will tarnish and acquire a warm patina with age, similar to the image below.



10 YEAR GUARANTEE

BRITISH MADE

## Declaration of Conformity

All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to identify latest version.

Date of Issue: 06th February 2022 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.