



# Data Sheet

Product Code: JDYP401S.PD

*This product can also be made using our Matrix System, using the products WDY1S.PD + MJP120 x 1*

---

**Product Description:** 1-Gang 2-Way Push-On/Off Rotary LED Dimmer 1 x 0-120W (1-10 LEDs)

---

**Range:** Screwless

**Finish:** Primed

**Product Category:** V-Pro Dimmer

**Insert/Knob Colour:** Chrome Knob

**Barcode:** 5021575192537

---

**Dimensions:** 86x86x48mm

**Faceplate Depth:** 4mm

**Net Weight:** 156g

**Gross Weight:** 158g

**Fixing Centres:** 60.3mm

**Depth from Mounting Face:**

**Recommended Back Box Depth:** 35mm

**Operating Voltage:** 230v 50Hz

**Maximum Load Rating:** LED; 120W (Max. 10 lamps)

**Maximum Current Rating:** 1.3A

**Terminal (Live) Diameter:** 3.2mm; **Capacity:** 3 x 1.5mm<sup>2</sup>

**Terminal (Earth) Diameter:** 3.3mm; **Capacity:** 3 x 1.5mm<sup>2</sup>

---

**Intended Applications:** Indoor Use Only. Domestic lighting circuits including many dimmable LEDs.

**Safety Advice:** Not suitable for use with non-dimmable fluorescent bulbs and tubes, wire-wound or toroidal transformers or electric motors. Do not overload. Product Must Be Earthed.



## Product Features

- ✔ V-Pro intelligent dimming technology
- ✔ Soft start feature and intelligent overload protection
- ✔ Adjustable minimum brightness setting and choice of driving modes
- ✔ Sleek, low-profile screwless faceplate
- ✔ For helpful tips on painting the Varilight Primed range, featuring different paints and methods, see our Varilight Primed - Best Practices article.



10 YEAR GUARANTEE

BRITISH MADE 

**Applicable Safety Standard:** BS EN 60669-2-1

**Commodity Code:** 85365005

Declaration of Conformity

*All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to identify latest version.*

*Date of Issue: 06th February 2022 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.*