



Data Sheet

Product Code: JFSE102

Product Description: 2-Gang 1-Way V-Pro Multi-Point Remote/Tactile Touch Control Master LED Dimmer 2 x 0-100W (1-10 LEDs)

Range: Ultraflat

Finish: Brushed Steel

Product Category: V-Pro Multi-Point Remote (formerly Eclique2)

Dimmei

Insert/Knob Colour: Steel Buttons

Barcode: 5021575622140

Dimensions: 89x89x26mm

Faceplate Depth: 1mm

Net Weight: 126g

Gross Weight: 128g

Fixing Centres: 60.3mm

Depth from Mounting Face: 23.2mm

Recommended Back Box Depth: 35mm

Operating Voltage: 230v 50Hz

Maximum Load Rating: LED; 100W (Max. 10 lamps)

Maximum Current Rating: 0.7A

Terminal (Live) Diameter: 3.2mm; Capacity: 3 x 1.5mm²
Terminal (Earth) Diameter: 3.3mm; Capacity: 3 x 1.5mm²

Intended Applications: Indoor Use Only. Domestic lighting circuits including many dimmable LEDs.

Note: Some LED lamps are not designed for electronic dimmer switches and may remain illuminated even when a dimmer switch is turned off. This can be corrected using one Varilight LEDFix load regulator per circuit (part number YAGF-P).



Product Features

⊘ V-Pro intelligent dimming technology


⊘ Soft start feature and intelligent overload protection

② 1-way or multi-way when used with Multi-Point dimming Supplementary Controller unit(s)

Ocontemporary, ultra-slim faceplate



10 YEAR GUARANTEE



Safety Advice: Not suitable for use with non-dimmable fluorescent bulbs and tubes, wire-wound or toroidal transformers, TRIAC dimmable loads or electric motors. Do not overload. Product Must Be Earthed.

Applicable Safety Standard: BS EN 60669-2-1

Commodity Code: 85365005

Declaration of Conformity

All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to identify latest version.

Date of Issue: 06th February 2022 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.