



Data Sheet

Product Code: JK1MO

Product Description: 1-Gang 2-Way Push-On/Off Rotary LED

Dimmer 1 x 0-120W (1-10 LEDs)

Range: Kilnwood

Finish: Medium Oak

Product Category: V-Pro Dimmer

Insert/Knob Colour: Medium Oak Knob

Barcode: 5021575966718

Dimensions: 96x96x53mm **Faceplate Depth:** 15mm

Net Weight: 126g Gross Weight: 128g Fixing Centres: 60.3mm

Depth from Mounting Face:

Recommended Back Box Depth: 25mm

Operating Voltage: 230v 50Hz

Maximum Load Rating: LED; 120W (Max. 10 lamps)

Maximum Current Rating: 1.3A

Terminal (Live) Diameter: 3.2mm; Capacity: 3 x 1.5mm²
Terminal (Earth) Diameter: 3.3mm; Capacity: 3 x 1.5mm²

Intended Applications: Indoor Use Only. Domestic lighting circuits including many dimmable LEDs.

Safety Advice: Not suitable for use with non-dimmable fluorescent bulbs and tubes, wire-wound or toroidal transformers, TRIAC dimmable loads or electric motors. Do not overload. Product Must Be Earthed.

⊏aiiiieu.

Applicable Safety Standard: BS EN 60669-2-1

Commodity Code:



Product Features

⊘ V-Pro intelligent dimming technology

⊘ Soft start feature and intelligent overload protection

 Adjustable minimum brightness setting and choice of driving modes

High grade sustainable timber



10 YEAR GUARANTEE

BRITISH MADE

Declaration of Conformity

All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to identify latest version.

Date of Issue: 06th February 2022 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.