



Data Sheet

Product Code: JK2LO

Product Description: 2-Gang 2-Way Push-On/Off Rotary LED Dimmer 2 x 0-120W (1-10 LEDs)

Range: Kilnwood

Finish: Limed Oak

Product Category: V-Pro Dimmer

Insert/Knob Colour: Limed Oak Knobs

Barcode: 5021575966756

Dimensions: 96x96x53mm

Faceplate Depth: 15mm

Net Weight: 156g

Gross Weight: 158g

Fixing Centres: 60.3mm

Depth from Mounting Face:

Recommended Back Box Depth: 25mm

Operating Voltage: 230v 50Hz

Maximum Load Rating: LED; 120W (Max. 10 lamps)

Maximum Current Rating: 0.9A

Terminal (Live) Diameter: 3.2mm; **Capacity:** 3 x 1.5mm²

Terminal (Earth) Diameter: 3.3mm; **Capacity:** 3 x 1.5mm²

Intended Applications: Indoor Use Only. Domestic lighting circuits including many dimmable LEDs.

Safety Advice: Not suitable for use with non-dimmable fluorescent bulbs and tubes, wire-wound or toroidal transformers, TRIAC dimmable loads or electric motors. Do not overload. Product Must Be Earthed.

Applicable Safety Standard: BS EN 60669-2-1

Commodity Code:



Product Features

- ✔ V-Pro intelligent dimming technology
- ✔ Soft start feature and intelligent overload protection
- ✔ Adjustable minimum brightness setting and choice of driving modes
- ✔ High grade sustainable timber



10 YEAR GUARANTEE

BRITISH MADE



Declaration of Conformity

All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to identify latest version.

Date of Issue: 06th February 2022 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.