



Data Sheet

Product Code: KQDP601W

This product can also be made using our Matrix System, using the products $WQD1W + MKP600 \times 1$

Product Description: 1-Gang 2-Way Push-On/Off Rotary LED

Dimmer 1 x 40-600W (max 60 LEDs) (Twin Plate)

Range: White

Finish: White Plastic

Product Category: V-Com Dimmer

Insert/Knob Colour: White Knob

Barcode: 5021575582345

Dimensions:~85x145x50mm

Faceplate Depth: 15mm

Net Weight: 209g

Gross Weight: 212g

Fixing Centres: 120.6mm

Depth from Mounting Face: 20.5mm

Recommended Back Box Depth: 25mm

Operating Voltage: 230v 50Hz

Maximum Load Rating: LED; 600W (Max. 60 LEDs)

Maximum Current Rating: 2.6A

Terminal (Live) Diameter: 3.2 mm; Capacity: $3 \times 1.5 mm^2$

Intended Applications: Indoor Use Only. Commercial & domestic lighting circuits including many dimmable LEDS.

Safety Advice: Not suitable for use with non-dimmable fluorescent bulbs and tubes, wire-wound or toroidal transformers or electric motors. Do not overload.

Applicable Safety Standard: BS EN 60669-2-1



Product Features

⊘ V-Com intelligent TRIAC leading edge dimming technology

⊘ Soft start feature and intelligent overload protection

② Adjustable minimum brightness setting and choice of driving modes to optimise the dimming performance of a given LED lighting load

O Durable white plastic



10 YEAR GUARANTEE



Commodity Code: 85365005

Declaration of Conformity

All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to identify latest version.

Date of Issue: 06th February 2022 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.