



Data Sheet

Product Code: KYP102.CU

This product can also be made using our Matrix System, using the products WY2.CU + MKP100 x 2

Product Description: 2-Gang 2-Way Push-On/Off Rotary LED Dimmer 2 x 0-100W (max 10 LEDs)

Range: Urban

Finish: Polished Copper

Product Category: V-Com Dimmer

Insert/Knob Colour: Polished Copper Knob

Barcode: 5021575966947

Dimensions: 91x91x47mm Faceplate Depth: 8mm Net Weight: 156g

Gross Weight: 158g Fixing Centres: 60.3mm

Depth from Mounting Face: 16.6mm Recommended Back Box Depth: 25mm

Operating Voltage: 230v 50Hz

Maximum Load Rating: LED; 100W (Max. 10 LEDs)

Maximum Current Rating: 0A

Terminal (Live) Diameter: 3.2mm; Capacity: 3 x 1.5mm² Terminal (Earth) Diameter: 3.3mm; Capacity: 4 x 1.5mm²

Intended Applications: Indoor Use Only. Commercial & domestic lighting circuits including many dimmable LEDS.

Safety Advice: Please note this product is not part of our Antimicrobial Copper range. Do not overload, not suitable for use with non-dimmable fluorescent bulbs and tubes, or electric motors. Product Must Be Earthed.

Applicable Safety Standard: BS EN 60669-2-1

Commodity Code: 85365005

Declaration of Conformity

All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to identify latest

Date of Issue: 08th March 2023 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.



Product Features

- **⊘** V-Com intelligent TRIAC leading edge dimming technology
- Soft start feature and intelligent overload protection
- ② Adjustable minimum brightness setting and choice of driving modes to optimise the dimming performance of a given LED lighting load
- ② Decorative copper finish with protective lacquer to prevent tarnishing



10 YEAR GUARANTEE

