



Data Sheet

Product Code: MKP100



② Can be used to replace dimmer modules in existing faceplates or in the Matrix

② Adjustable minimum brightness setting and choice of driving modes to optimise

⊘ V-Com intelligent TRIAC leading edge dimming technology

⊘ Soft start feature and intelligent overload protection

the dimming performance of a given LED lighting load

Product Description: 2-Way Push-On/Off Rotary LED Dimmer 0-100W (max 10 LEDs)

Range: Module Finish: Matrix

Product Category: V-Com Module

Barcode: 5021575003970

Dimensions: 52x26x42mm (Click here to see full dimensions)

Net Weight: 48g Gross Weight: 50g Fixing Centres: N/A

Depth from Mounting Face: 0

Recommended Back Box Depth: N/A

Operating Voltage: 230v 50Hz

Maximum Load Rating: LED; 100W (Max. 10 LEDs)

Maximum Current Rating: 0.4A

Terminal (Live) Diameter: 3.2mm; Capacity: 3 x 1.5mm²

Intended Applications: Indoor Use Only. Commercial & domestic lighting circuits including many dimmable LEDS.

Safety Advice: Not suitable for use with non-dimmable fluorescent bulbs and tubes, wirewound or toroidal transformers or electric motors. Do not overload.

Applicable Safety Standard: BS EN 60669-2-1

Commodity Code: 85365005

BRITISH MADE

1 YEAR GUARANTEE

Product Features

dimmer grid system

Declaration of Conformity

All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to identify latest version.

Date of Issue: 06th February 2022 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.