



Data Sheet

Product Code: TESP401S

Product Description: 1-Gang 2-Way Push-On/Off Rotary Dimmer 1 \times

60-400W

Range: European

Finish: Brushed Steel

Product Category: V-Dim Dimmer

Insert/Knob Colour: Steel Knob

Barcode: 5021575030464

Dimensions: 86x86x47mm

Faceplate Depth: 4mm

Net Weight: 146g

Gross Weight: 148g

Fixing Centres: 60.3mm

Depth from Mounting Face: 23mm

Recommended Back Box Depth: Standard European 40mm Round

or Square

Operating Voltage: 230v 50Hz

Maximum Load Rating: Halogen; 400W

Maximum Current Rating: 1.7A

Terminal (Live) Diameter: 3.2mm; Capacity: 3 x 1.5mm²

Terminal (Earth) Diameter: 3.3mm; Capacity: 3 x 1.5mm²

 $\label{lem:condition} \textbf{Intended Applications:} \ \textbf{Indoor Use Only.} \ \textbf{Domestic lighting circuits.}$

Safety Advice: Not suitable for wire-wound low voltage transformers,

fluorescent lighting, motors or fans. Do not overload.

Applicable Safety Standard: BS EN 60669-2-1

Commodity Code: 85365007

Product Features

V-Dim dimming technology

 $oldsymbol{\Theta}$ Overload protection that automatically switches off the lights when an overload is detected

⊘ Sleek, low-profile faceplate

10 YEAR GUARANTEE

BRITISH MADE

Declaration of Conformity

All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to identify latest version.

Date of Issue: 06th February 2022 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.