

Data Sheet

Product Code: XT5U2B

Product Description: 2-Gang 13A Unswitched Socket + 2x5V DC

2100mA USB Charging Ports

Range: Classic

Finish: Brushed Steel

Product Category: 13A Socket + USB

Insert/Knob Colour: Black Inserts

Barcode: 5021575032314

Dimensions: 91x150x28mm

Faceplate Depth: 8mm

Net Weight: 209g

Gross Weight: 212g

Fixing Centres: 120.6mm

Depth from Mounting Face: 18.5mm

Recommended Back Box Depth: 25mm

Operating Voltage: 230v 50Hz

Maximum Load Rating: 13A

Maximum Current Rating: 13A

Terminal (Live) Diameter: 4.8 mm; Capacity: $4 \times 2.5 \text{mm}^2$

Terminal (Neutral) Diameter: $4.8 \, \text{mm}$; Capacity: $4 \times 2.5 \, \text{mm}^2$

Terminal (Earth) Diameter: 4.8mm; Capacity: 4 x 2.5mm²

Intended Applications: Indoor Use Only. Domestic power supply.

Safety Advice: Please note recommended back box depth relies on

efficient cable routing.. Product Must Be Earthed.

Applicable Safety Standard: BS 1363-2

Commodity Code: 85366990



Product Features

❷ Ideal for charging iPad, iPhone, tablets, mobiles and cameras

❷ Features VARILIGHT Smart Port technology making it suitable for all types of devices.

② The USB port detects the device to be charged and optimises its output accordingly to achieve the fastest possible charging speed.

Bevelled edge faceplate



10 YEAR GUARANTEE

BRITISH MADE

Declaration of Conformity

All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to identify latest version.

Date of Issue: 06th February 2022 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.