

Data Sheet

Product Code: XT6UFOD

Product Description: 13A Unswitched Fused Spur + Flex Outlet with

Metal Inserts

Range: Classic

Finish: Brushed Steel

Product Category: Fused Spur

Insert/Knob Colour: Steel Inserts

Barcode: 5021575032482

Dimensions: 91x91x34mm

Faceplate Depth: 8mm

Net Weight: 166g

Gross Weight: 168g

Fixing Centres: 60.3mm

Depth from Mounting Face: 17.2mm

Recommended Back Box Depth: 25mm

Operating Voltage: 230v 50Hz

Maximum Load Rating: Refer to Fuse Value

Maximum Current Rating: 13A

Terminal (Live) Diameter: $4.5 \, \text{mm}$; Capacity: $4 \times 2.5 \, \text{mm}^2$ Terminal (Neutral) Diameter: $4.5 \, \text{mm}$; Capacity: $4 \times 2.5 \, \text{mm}^2$

Terminal (Earth) Diameter: 3.3 mm; Capacity: $3 \times 1.5 mm^2$

Intended Applications: Indoor Use Only. Domestic power supply.

Safety Advice: Product Must Be Earthed.

Applicable Safety Standard: BS 1363-4

Commodity Code: 85389091



Product Features

- O Holds standard 25.4x6.4mm fuse
- Bevelled edge faceplate



10 YEAR GUARANTEE

BRITISH MADE

All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to identify latest version.

Date of Issue: 06th February 2022 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.