

TKE/P 50 LG



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

| | |
|---------------------------------|---------------------------|
| Material cable gland | Polyamide |
| Material sealing gasket | EPDM |
| Temp. range min | -40 °C |
| Temp. range max | 100 °C |
| Protection class | IP66, IP68 (5 bar 30 min) |
| Product Color | RAL 7035 |
| Thread type | M |
| Ø Connection thread D | 50 |
| Lead | 1,5 |
| Length screw-in thread L | 14 mm |
| Key width SW | 55 mm |
| Total length TL | 59 mm - 72 mm |
| Glow wire test | 750 °C |
| Type of cable anchorage | A |
| Install. torques fitting | 30 N/m |
| Install. torques cap nut | 30 N/m |
| Impact category | 5 |
| Order no. RAL 7035 | 10106246 |
| Type | TKE/P 50 LG |
| Packing unit | 1 |
| ETIM-Classification | EC000441 |

Description:

IP68 Plastic Cable gland kit,
 ESKV 50 with MFD Multi Hole insert suitable for 3 phase applications with 4 x 25mm Tails and 1 x 16mm earth

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708



info@wiska.co.uk · www.wiska.co.uk

02.06.2023

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

 +44-12-08816062 ·  +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk