

# electrium



Miniature SPD  
Overvoltage Protection  
Device

# MINIATURE SPD FOR SURGE PROTECTION IN DOMESTIC HOUSEHOLD PREMISES

## SINGLE MODULE SPD

At just **18mm wide** this miniature SPD leaves more ways for household circuits and allows the most compact consumer unit to be used.

## FULLY RATED 100A

No need for additional back up device in the consumer unit.

## SIMPLE TO INSTALL

Connects directly onto the busbar (just like an MCB) supplied with Neutral and Earth cable connections.

## LESS WIRING

Fewer cable links to connect than alternative products, which speeds up installation.

## TYPE 2 SURGE PROTECTION

With status indicator and volt free contacts for remote monitoring and/or signalling.

## SECURE CARTRIDGE ASSEMBLY

Cartridges are securely locked into place and cannot be removed for replacement without use of a tool.


## CERTIFIED AS FULLY COMPLIANT


Wylex single module SPDs are designed, manufactured & tested to IEC EN61643-11 and certified as compliant.

## RETROFIT COMPATIBLE

Fits metal NM & insulated NH consumer units\* (includes a balcony busbar connection). Supplied with a retrofit circuit icons label pack.

\* Not suitable for Dual RCD configurations





**NMT2SPD3W/1**



**NMT2SPD/P**

### SURGE PROTECTION DEVICE

CAT REF	DESCRIPTION
<b>NMT2SPD3W/1</b>	Single Module Type 2 SPD

- Suitable for all Single Phase 3 Wire Systems TN-C-S, TN-S and TT
- Clear Indication of device status
- Fitted with remote signalling contact
- Suitable for use in Main Switch, Split Load & Hi-Integrity consumer unit configurations
- Not suitable for Dual RCD configurations

Alternative SPD products are available for Dual RCD consumer unit installations. Please contact Wylex technical for further assistance.

### TECHNICAL DATA

<b>Product Standard</b>	IEC EN 61643-11
<b>Nominal discharge surge current (8/20) <math>\mu</math>s</b>	20kA
<b>Short-circuit breaking capacity (I<sub>sc</sub>cr)</b>	25kA
<b>Max. continuous voltage AC</b>	275V
<b>Max. discharge surge current (8/20) <math>\mu</math>s</b>	40kA
<b>Voltage protection level</b>	1.3 kV
<b>Voltage protection level L-N</b>	1.3 kV
<b>Voltage protection level N-PE</b>	1.3 kV
<b>Max. conductor cross section (solid / stranded)</b>	25mm <sup>2</sup>
<b>Degree of protection</b>	IP20
<b>Dimensions</b>	Height 85mm x Width 18mm x Depth 70mm

### REPLACEMENT PLUG-IN CARTRIDGE

CAT REF	DESCRIPTION
<b>NMT2SPD/P</b>	Replacement Plug-in Cartridge for <b>NMT2SPD3W/1</b>

- Combined Metal Oxide Varistor (L1 & N) and Gas Discharge Tube (N & E)

# electrium

## **ELECTRIUM SALES LIMITED A SIEMENS COMPANY**

Commercial Centre, Lakeside Plaza,  
Walkmill Lane, Bridgtown,  
Cannock WS11 0XE.  
eMail: [info@electrium.co.uk](mailto:info@electrium.co.uk)

[www.electrium.co.uk](http://www.electrium.co.uk)

### **UK SALES**

Telephone: 01543 455020  
Facsimile: 01543 455021  
eMail: [wylex.sales@electrium.co.uk](mailto:wylex.sales@electrium.co.uk)

### **TECHNICAL**

Telephone: 01543 438320  
Facsimile: 01543 438321  
eMail: [wylex.technical@electrium.co.uk](mailto:wylex.technical@electrium.co.uk)

### **EXPORT SALES**

Telephone: +44 1543 455049  
Facsimile: +44 1543 455048  
eMail: [export@electrium.co.uk](mailto:export@electrium.co.uk)

### **DUBAI OFFICE**

Telephone: +971 4 3660684  
Facsimile: +971 4 3660676  
eMail: [export@electrium.co.uk](mailto:export@electrium.co.uk)



[@ElectriumNews](https://twitter.com/ElectriumNews) or download the APP

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this publication, specifications and performance data are constantly changing. Users should always consult the installations instructions, IET wiring regulations and all other relevant documents, and not solely rely on information in this catalogue.

Publication No. WY2604 03/2021

# #63

Surge Protection - safeguarding your data and productivity.

