



Zip filtered water

Filtered chilled or ambient water



Zip Trio – Mixer tap and filtered water



Zip FilterTap

Delivery rate (chilled water)

Up to 4 glasses at a time

Recovery rate (chilled water)

Up to 25 glasses/hour*

*Dependant upon incoming water temperature and ambient air temperature

Features

- Zip Trio provides hot and cold water and filtered drinking water
- Zip Trio replaces conventional mixer taps (or separate hot and cold taps)
- Zip FilterTap provides filtered drinking water
- Healthy, clean, chilled drinking water instantly
- Everything but the tap hidden beneath the work top
- No more bottled water to buy or store
- Chilled or ambient options available on Trio and FilterTap

01.03.08



Model	Product Code	Delivery glasses at a time	Recovery glasses/hour	Energy Rating (kW @ 230V)	Chiller Unit Weight (kg)	Chiller Dimensions H x W x D (mm)
Zip Trio (chilled chrome)	DOMT1	4	25	0.18	13	192 x 295 x 396
Zip Trio (chilled nickel)	DOMT2	4	25	0.18	13	192 x 295 x 396
Zip Trio (ambient chrome)	DOMT3	unlimited	unlimited	N/A	N/A	—
Zip Trio (ambient nickel)	DOMT4	unlimited	unlimited	N/A	N/A	—
Zip FilterTap (chilled chrome)	DOMT6	4	25	0.18	13	192 x 295 x 396
Zip FilterTap (ambient chrome)	DOMT5	unlimited	unlimited	N/A	N/A	—

Details

- Trio provides mixed hot and cold domestic water together with filtered drinking water
- Undersink instant ambient or chilled water
- Trio available as chrome or brushed nickel finish
- Submicron triple action filtration
- Components other than the tap in a single case with filter housing located separately within the cupboard space

Chilled system

Delivery temperature – 5-10°C

Tank construction – stainless steel

Compressor – 1/16hp

Minimum pressure – 1.0 bar

Maximum pressure – 3.5 bar

Refrigerant – R143a

Flow rate – 1.6 litre/min

Chilled and Ambient systems

Fittings – John Guest push fit

Tubing – 1/4" flexible

Mains connection – saddle valve with integral non-return valve

Filter – submicron, triple action (taste, odour and chlorine reduction)

Filter capacity – 6000 litres

Filter head – cast metal with integral shut off valve for easy filter change

Tap Head

Chrome plated on FilterTap, chrome or brushed nickel on Trio

Approvals

WRAS Approval on chiller unit

Warranty

12 months

Installation

Location

The tap should be positioned either on a suitable sink or on a worktop, draining into a sink

The chiller unit should be located as closely as possible beneath the tap

The filter head should be fitted within a suitable distance from the saddle valve with the cartridge hanging vertically

A 21mm hole should be drilled to take the FilterTap and 35mm hole for Trio

The chiller unit must be installed with clearances of 50mm left and right

Plumbing

The water supply must be potable (drinkable)

If static pressure exceeds 3.5 bar, a pressure reducing valve must be fitted

An isolating valve is incorporated into the saddle clamp provided

Electrical

To be wired to a double pole fused spur, minimum break rating of 13 amps

Installation must comply with current IEE regulations

Technical Support

Contact Zip on 0800 077 8302

Chart showing comparison of Zip submicron filtration v 5 micron

Type	Chlorine reduction	Taste & Odour	Sediment reduction	Cyst reduction	Performance
Submicron	●	●	●	●	99.99%
5 micron	●	●	●		85%

01.03.08