

Instantaneous Handwash Unit

Zip Handwash™

Warm water for hand washing, instantly and continuously

Single valve controls flow and temperatures

Swivel spout with unidirectional sprayhead

Escutcheon conceals plumbing connections

No special wiring, connects into 13 amp ring main



Description

- Type: open outlet instantaneous handwash heater
- Capacity: continuous flow
- Rating: 3.0 kW
- Heating element: embedded rod type
- Case: high impact resistant white plastic
- Pressure switch: minimum operational pressure 7 psi, maximum 90 psi
- Safety features: over temperature safety cutout
- Approvals: CE endorsed – WRAS approved

Installation

Model	Electrical Information	Dimensions (mm)			Minimum Pressure	Maximum Pressure
		A	B	C		
SHH-3	3.0 kW 230/240 v 13 amp	300	180	85	7 psi	90 psi

Sample specification guide

Handwash Heater, model number SHH-3, designed to comply with the following specification

1. To be fitted with a 3.0 kW element
2. To have a white plastic outer case
3. To have a thermal cut-out
4. To operate with a minimum water pressure of 7 psi
5. To have a removable escutcheon to conceal plumbing connections
6. To have a swivel spout with multidirectional sprayhead
7. To be WRAS approved and CE endorsed

TYPICAL INSTALLATION

