



TS-7 - Push button timer – 6kW

Application	Controlling halogen heaters (including patio heaters) and ceramic heaters
Mounting	Surface
Time delay	5 minutes to 90 minutes
Switching capacity	6kW 230V (250W minimum)
Voltage supply	230V
Contacts	Single pole, single throw
Dimensions	124mm x 124mm x 78mm
Ingress protection	IP65
Special features	Constant light indicates 'heater on' Flashing light indicates last minute of operation Can be used with our PROTIM-7 timer or a volt free thermostat such as our PROSTAT2 Soft start switching prolongs halogen lamp life Supplied with 2 x M20 cable glands



TS-6 - Push button timer - 3kW

Application	Controlling halogen heaters (including patio heaters) and ceramic heaters
Mounting	Surface
Time delay	2 minutes to 2 hours
Switching capacity	16A 230V
Voltage supply	230V
Contacts	Single pole, single throw
Dimensions	85mm x 85mm x 67mm
Ingress protection	IP66
Special features	Touch activated Blue light indicates heating off Red light indicates 1minute operation remaining



PROTIM-7 - Programmable timer

Application	Ideal for use with a variety of commercial and industrial heating schemes
Programming	7day, 5 + 2 days or 24hour
Mounting	Surface
Maximum events per day	4
Switching Capacity	13A 230V (when switching halogen heaters this timer can be used in conjunction with our SSR soft start relay – see page 79)
Voltage Supply	230V
Dimensions	90 x 115 x 57mm
Ingress Protection	IP30
Special Features	Advance to next programme Boost (select 1 hour or 2 hours) Override – permanently on or permanently off Automatic summer update Battery back up Tough aluminium case