

IRCAM600

External use Varifocal Day / Night Bullet Camera

Features

- Integral LED Illumination (30m)
- Colour in Day - Mono in darkness
- Varifocal Manual 4 to 9mm Lens
- 580TVL Horizontal Resolution

Signal System	PAL
Effective Pixels	752(H) x 582(V)
Image sensor	1/3" SONY Super HAD CCD
Sensing Area	4.9mm x 3.7mm
Shutter Speed	1/50(1/60) ~ 1/100,000 SEC
Video Output	1.0Vp-p,75Ω
Scanning Frequency	Horizontal: 15.62KHz / Vertical: 50Hz
Scanning System	2:1 interlace / internal
Horizontal Resolution	580 TV Lines
Minimum Illumination	0.01Lux (F1.2)/0.00LUX(inIR Mode)
Gamma Correction	0.45
S/N Ratio	≥ 50dB (AGC OFF)
White Balance	Automatic White Balance
AGC	ON
BLC	ON
IR Capability	42 pcs ϕ 5 IR-LED
IR Illumination Distance	More than 30m
Operating Temp:	-10~50℃
Water Resistance	IP 66
Lens	4 to 9mm Manual Varifocal
Dimensions (cms)	
Weight (kgs)	
Power Source	DC12V
Power Consumption	120mA (IR OFF), 400mA (IR ON)