

Technical Specification

Product Code: APWIFIDS2

Description: Mains Wi-Fi Door Station with Record Facility







Component 1 Wi-Fi (Wired) Door Station with Record Facility

Component 2 Wireless Chime Quantity

General Information	
Dimensions (mm) 132 x 55 x 24
Finisl	n Silver
Materials	Aluminium & Polycarbonate
Audio	Full Duplex
Number of LED's	s 5
Sensor Size (") 1/2.7
Low Light Level Viewing Distance (m) 5
Backligh	t Around Push Button
Status Indication	Red or Blue (Around push button)
Maximum IR Distance (m) 5
Supply & Power	
Operating Voltage (V DC)	9 - 48
Bell Contact	Normally Open; Volt-Free
Bell Contact, Maximum Load	24V DC @ 2A
Commontion Time	[tla a was at 0 \A/! [:

Supply & Fower	
Operating Voltage (V DC)	9 - 48
Bell Contact	Normally Open; Volt-Free
Bell Contact, Maximum Load	24V DC @ 2A
Connection Type	Ethernet & Wi-Fi
Lock outputs	1

Medi	a Information
	Populutio

Resolution	1920 x 1080
Sensitivity (Lux)	1
Viewing Angle (°)	140
Frames Per Second (FPS)	20
Recording	

Recording Storage Device | Micro SD Card (128GB Max.)

User Interaction	Single Call Button
Programming Type	App Based
atwork	

Network

- Itothorik	
Recommended BUS Cable	Cat5e or Higher
Wireless Range - Open Field (m)	150
	Ethernet VIA 4 of 8 cores of Cat5e (or higher) [RD-, TD+, RD- & RD+]

Inputs & Outputs

Dry Lock Output	Normally Open Relay (Volt-
	Free)
Dry Lock Output, Maximum Load	24V DC @ 2A
Relay Types	Normally Open

Envi

ironment	
Ingress Protection	IP55
Operating Temperature (°C)	-10 to 40

Unit 7 Target Park, Shawbank Road, Lakeside, Redditch B98 8YN United Kingdom **T:** +44 (0)1527 515150 | **F:** +44 (0)1527 515143 E: info@espuk.com | W: espuk.com

General Information	
Dimensions (mm)	153 x 60 x 26
Finish	Grey & White
Materials	ABS
Operating Battery	3 x AA
Bell Contact	Normally Open; Volt-Free
Connection Type	RF
User Interaction	3 Buttons; Volume, Ringtone, and Configuration
Ingress Protection	IP20
Operating Temperature (°C)	-10 to 40





Technical Specification



Product Code: APWIFIDS2

Description: Mains Wi-Fi Door Station with Record Facility

Supplied Doorstation and Wall Bracket

RF Door Chime

2 x Fixing Screws & Wall Plugs Plug-in Power Adapter 8GB MicroSD Card DC Power Extension cable 2 x Relay Contact Extension cables

Terminal Screwdriver RF Door Chime 3 x AA Batteries Quick Start Guide

Additional Information Ethernet Interface Available

Alerts users to visitors VIA smart-phone app

No additional subscriptions or fees

Visitor Record Function, Smart Detection (Motion Detection)

High Definition Colour Image, and 2 way audio

Accessories

EVBPSBB: 12V Lock power supply with battery backup

