

Technical Specification

Description: Mains Wi-Fi Door Station with Record Facility





Quantity



Component 1 Wi-Fi (Wired) Door Station with Record Facility **Component 2** Wireless Chime Quantity

General Information

Dimensions (mm)	132 x 55 x 24	
Finish	Black	
Materials	Aluminium & Polycarbonate	
Mounting	Surface Only	
Audio	Full Duplex	
Number of LED's	5	
Sensor Size (")	1/2.7	
Low Light Level Viewing Distance (m)	5	
Backlight	Around Push Button	
Status Indication	Red or Blue (Around push button)	
Maximum IR Distance (m)	5	
Supply & Power		
Operating Voltage (V DC)	9 - 48	

11 7	
Operating Voltage (V DC)	9 - 48
Bell Contact	Normally Open; Volt-free
Bell Contact, Maximum Load	24V DC @ 2A
Connection Type	Ethernet & Wi-Fi
Lock outputs	1
Marilla Indonesia Mari	

Media Information		
Resolution	1920 x 1080	
Sensitivity (Lux)	1	
Viewing Angle (°)	140	
Frames Per Second (FPS)	20	
Programming		
User Interact	tion Single Call Button	

Programming Type | App Based

Network	
Recommended BUS Cable	Cat5e or Higher
Wireless Range - Open Field (m)	150
Network Connection	Ethernet VIA 4 of 8 cores of Cat5e (or higher) [RD-, TD+, RD- & RD+]

Inputs & Outputs

·		
Dry Lock Οι	ıtput	Normally Open Relay (Volt-
		Free)
Dry Lock Output, Maximum L	oad	24V DC @ 2A
Relay Types		Normally Open
Environment		
Ingress Protection	IP55	
Operating Temperature (°C)	-10 to	0 40

General Information	
Dimensions (mm)	153 x 60 x 26
Finish	Grey & White
Materials	ABS
Operating Battery	3 x AA
Bell Contact	Normally Open; Volt-Free
Connection Type	RF
User Interaction	3 Buttons; Volume, Ringtone, and Configuration
Ingress Protection	IP20
Operating Temperature (°C)	-10 to 40





Technical Specification



Product Code: APWIFIDSBLK2

Description: Mains Wi-Fi Door Station with Record Facility

Supplied Doorstation and Wall Bracket

RF Door Chime

2 x Fixing Screws & Wall Plugs Plug-in Power Adapter 8GB MicroSD Card DC Power Extension cable

2 x Relay Contact Extension cables

Terminal Screwdriver RF Door Chime 3 x AA Batteries Quick Start Guide

Additional Information Ethernet Interface Available

Alerts users to visitors VIA smart-phone app

No additional subscriptions or fees

Visitor Record Function, Smart Detection (Motion Detection)

High Definition Colour Image, and 2 way audio

Accessories

EVBPSBB: 12V Lock power supply with battery backup

