

**Product Code:** MAG2

**Description:** 2 Zone Metal Conventional Fire Panel



### General Information

<b>Dimensions</b>	200mm x 290mm x 80mm
<b>Max Detectors Per Zone</b>	20
<b>Thresholds for Zone Conditions</b>	0 - 2 mA (Fault condition) 2 - 6 mA (Normal condition) 6 - 110 mA (Fire condition)
<b>Call Points Per Zone</b>	Unlimited
<b>Weight</b>	2.7kg (without battery)

### Outputs

<b>Sounder 1</b>	24V (max 300mA fused)
<b>Sounder 2</b>	24V (max 300mA fused)
<b>Fault/Fire Relay</b>	Volt free 500mA @ 24V (max load)
<b>Auxiliary Output</b>	24VDC (300mA fused)

### Power

<b>Mains Fail Consumption</b>	50mA
<b>Mains Supply</b>	230 VAC ± 10%
<b>Standby Supply</b>	Up to 12V 7Ah (Battery Calculation Required)
<b>Power Availability</b>	0.7 amps

### Environment

<b>Relative Humidity Resistance</b>	(93±3)% @ 40°C
<b>Storage Temperature</b>	-20°C to 60°C
<b>Operating Temperature</b>	-5°C to +40°C

### Additional Features

- Integral sound alarm button
- Enable/disable security key
- One man walk test facility
- Individual sounder circuit fault ID
- Individual zone/sounder isolate
- Class change' facility

### Accessories

<b>BAT7</b>	12V 7Ah SLA Battery
<b>MAGBAR2/4</b>	Key & Barrel set