

Product Code: H512VDWA

Description: HDview IP PoE Varifocal 2.8-12mm Motorised Lens Dome Camera Anti-Vandal White



### General Information

Dimensions (mm)	128 x 100 x 128
Finish	White & Black
Materials	Metal & Polycarbonate
Mounting	Surface
Impact Rating (IK)	IK10
Weight (Kg)	0.66
Warranty (Years)	3

### Recording

Storage Type	Micro SD, up to 256 GB
--------------	------------------------

### Environment

Ingress Protection	IP67
--------------------	------

### Supply & Power

Operating Voltage (V DC)	12
Power Consumption (W)	8
Other Power Sources	PoE (IEEE802.3af)

### Media Information

Sensor Size (")	1/2.7" Progressive CMOS
Lens size (mm)	2.8-12
Lens Type	Varifocal (Motorised)
Viewing Angle (°)	96.4 - 32.7
Electronic Shutter Type	Auto / Manual
Speed (sec/°)	1 to 1/100000
Scanning System	Progressive Scan CMOS
Frames Per Second (FPS)	5MP (2880*1620), Max 25fps 4MP (2560*1440), Max 25fps 3MP (2304*1296), Max 30fps 1080P (1920*1080), Max 30fps
Maximum IR Distance (m)	40
IR Wavelength (nm)	850
Video Bit Rate	128 Kbps - 8 Mbps
Microphone Supported	Built-in
Day/Night	IR-Cut filter with Auto Switch (ICR)
Basic Detection	Cross line, intrusion(based on human body detection), Motion Detection, Ultra Motion Detection, Tampering alarm, Audio Detection
Intelligent Detection	Watermark, IP Address Filtering, Access Policy, ARP Protection, RTSP Authentication, User Authentication, HTTP authentication

### Network

Interface	1 RJ45; 10/100M Base-TX Ethernet
ONVIF Compliant	Yes; Profile S, Profile G, Profile T
Network Functions	IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SNMP, QoS, RTMP,SSL/TLS

**Supplied** Quick Start Guide, Mounting Guide, Installation Screws and Rawlplugs and Pass Through Gland

**Compatible Products** The range of 24/7 Network Video Recorders 4, 8, 16, 32 and 64 Channels

### Accessories

DBW4: HDview IP 5MP Dome Deep Base White

