Illuma

Lumapar TM3411

Sills Road Willow Farm Business Park F: +44(0)1332 818 222 Derbyshire DE72 2US United Kingdom

T: +44(0)1332 818 200 E: info@illuma.co.uk W: www.illuma.co.uk

product data sheet

	Description A flexible range a transformer. I
APPLICATIONS	Ideal for highlig applications, pa
SALES FEATURES	αρριτατιστις, μα

of discreet spotlights for mains tungsten halogen lamps not requiring deal for highlighting and general lighting applications.

APPLICATIONS	Ideal for highlighting and general lighting in retail, commercial and domestic applications, particularly where unobtrusive miniature fittings are required.
SALES FEATURES	
Comprehensive range	Two styles; standard track versions for use with Illuma 1-circuit track; surface- mounting versions. Other track versions can be made to order: for use with certain types of Concord, Global and Thorn 1-circuit track (order TM3411/G1 etc); for use with Global 3-circuit track (order TM3411/G3 etc). White finish.
Quality	Suitable for direct mounting on flammable surfaces. Guaranteed for five years.
Ease of installation	Easy installation and removal from track. The adaptor locks the spotlight positively to the track, and on standard versions incorporates a switch for individual switching. Surface spotlights are pre-wired to a 10A terminal block.
Lamp description	Energy Saving Minature compact Fluorescent



Sills Road Willow Farm Business Park Derbyshire DE72 2US United Kingdom


T: +44(0)1332 818 200 F: +44(0)1332 818 222 E: info@illuma.co.uk W: www.illuma.co.uk

TECHNICAL SPECIFICATION

Technical Data

Cut out dia. (mm) IP Rating Weight (kgs) Input Voltage(V) Dimming

0
20
0.14
240v
Not suitable for Dimming



MATERIALS

Body	Diecast Aluminium
Stem	Diecast Aluminium
Lampholder	Ceramic
Wiring	PTFE coated
Finish	Powder Coated

LAMP DATA

L	_amp Type	Lamp Cap	No.	Lamp Watts	Lamp Current	Lamp Lumens	Lamp Life
F	PAR16 CFL	GU10	1	14	0.1	300	15000