
# **Knightsbridge**

### DATASHEET

### **BATCA6EM**

#### 230V 6ft 40W LED CCT Batten Emergency

www.mlaccessories.co.uk



| MLA PART CODE                 | BATCA6EM   |
|-------------------------------|--|
| DESCRIPTION                   | 230V 6ft 40W LED CCT Batten Emergency                            |
| NET WEIGHT (KG)               | 2.1  |
| FINISH                        | White  |
| DIFFUSER                      | Opal   |
| DIMENSIONS (MM)               | Length - 1734<br>Height - 61<br>Width - 71                       |
| CONSTRUCTION                  | Construction - Pressed steel<br>Construction 2 - & polycarbonate |
| CLASS                         |  |
| IP RATING                     | IP20   |
| WATTAGE (W)                   | 40   |
| LAMP TECHNOLOGY               | SMD LED  |
| LAMP INCLUDED                 | Yes  |
| LUMENS (LM)                   | 4905/5370/4910   |
| LUMENS LIGHT SOURCE ONLY (LM) | 5990   |
| LUMEN TOLERANCE               | 5%   |
| EFFICACY (LM/W)               | 127.2  |
| LUMENS EMERGENCY MODE (LM)    | 230  |
| CIRCUIT WATTAGE (W)           | 42.2   |
| ССТ                           | 3000/4000/6000K  |
| LIGHT COLOUR                  | ССТ  |
| CRI                           | >85  |
| SDCM                          | <6   |
| RUNNING CURRENT (A)           | 0.19   |
| DISPLACEMENT FACTOR           | >0.7   |



ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification. ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.



# **Knightsbridge**

| SVM                                      | 0.006   |
|--|---|
| PST-LM                                   | 0   |
| BEAM ANGLE (DEGREES)                     | 140   |
| L70B50 LIFESPAN (HRS)                    | 50,000  |
| DIMMABLE                                 | No  |
| EMERGENCY                                | Maintained / Non-maintained / Switched  |
| SELF-TEST                                | No  |
| OPERATING TEMPERATURE                    | -20~45°C  |
| INPUT VOLTAGE                            | 230V 50Hz   |
| CABLE GLAND INCLUDED                     | Open grommet  |
| DRIVER                                   | DRIVER TYPE - Constant Current<br>MAX. OUTPUT - 40W<br>OUTPUT VOLTAGE - 28-40V<br>OUTPUT CURRENT - 1000mA<br>POWER FACTOR - 0.95<br>AMBIENT TEMPERATURE (Ta) - 45°C<br>CASE TEMPERATURE (Tc) - 90°C |
| BATTERY INCLUDED                         | Yes   |
| WARRANTY                                 | 5year(s)  |
| WARRANTY INFORMATION                     | (excluding battery)   |
| ORIGIN OF MANUFACTURE                    | China   |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes   |
| EAN                                      | 5056270886382   |
| Date Created: 26/07/2022 16:28           |   |

Date Created: 26/07/2022 16:28





