Knightsbridge

DATASHEET



FP1200BB

Flat Plate 10AX 1G Intermediate Switch - Brushed Brass

www.mlaccessories.co.uk

NET WEIGHT (KG)0.08SINISHBrushed BrassDIMENSIONS (MM)Height - 87.5 Width - 87.5 Projection - 2.5MINIMUM MOUNTING BOX DEPTH16mmCONSTRUCTIONConstruction - Premium grade steelCLASSIP RATINGIP20NPUT VOLTAGE230V 50HzSWITCH FUNCTIONIntermediateCARTH TERMINALYesLOAD/MAX. LOAD10AXTERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²VARRANTY15year(s)MANUFACTURED IN ACCORDANCE WITHBS EN 60669-1DRIGIN OF MANUFACTUREYesDECLARATION OF CONFORMITY (HELD ON FILE)Yes	MLA PART CODE	FP1200BB
FINISHBrushed BrassDIMENSIONS (MM)Height - 87.5 Width - 87.5 Projection - 2.5MINIMUM MOUNTING BOX DEPTH16mmCONSTRUCTIONConstruction - Premium grade steelCLASSIP RATINGIP20NPUT VOLTAGE230V 50HzSWITCH FUNCTIONIntermediateCARTH TERMINALYes.OADI/MAX. LOAD10AXTERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²NARRANTY15year(s)MANUFACTURED IN ACCORDANCE WITHBS EN 60669-1DECLARATION OF CONFORMITY (HELD ON FILE)Yes	DESCRIPTION	Flat Plate 10AX 1G Intermediate Switch - Brushed Brass
DIMENSIONS (MM)Height - 87.5 Width - 87.5 Projection - 2.5MINIMUM MOUNTING BOX DEPTH16mmCONSTRUCTIONConstruction - Premium grade steelCLASSIP RATINGIP20NPUT VOLTAGE230V 50HzSWITCH FUNCTIONIntermediateCARTH TERMINALYes.OAD/MAX. LOAD10AXTERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²VARRANTY15year(s)MANUFACTURED IN ACCORDANCE WITHBS EN 60669-1DRIGIN OF MANUFACTUREChinaDECLARATION OF CONFORMITY (HELD ON FILE)Yes	NET WEIGHT (KG)	0.08
DIMENSIONS (MM)Width - 87.5 Projection - 2.5MINIMUM MOUNTING BOX DEPTH16mmCONSTRUCTIONConstruction - Premium grade steelCLASSIP RATINGIP20NPUT VOLTAGE230V 50HzSWITCH FUNCTIONIntermediateEARTH TERMINALYesCOAD/MAX. LOAD10AXTERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²NARRANTYI5year(s)MANUFACTURED IN ACCORDANCE WITHBS EN 60669-1CRIGIN OF MANUFACTUREYesCOADFORMITY (HELD ON FILE)Yes	FINISH	Brushed Brass
CONSTRUCTIONConstruction - Premium grade steelCLASSIP RATINGIP20NPUT VOLTAGE230V 50HzSWITCH FUNCTIONIntermediateEARTH TERMINALYes.OAD/MAX. LOAD10AXTERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²NARRANTY15year(s)MANUFACTURED IN ACCORDANCE WITHBS EN 60669-1DECLARATION OF CONFORMITY (HELD ON FILE)Yes	DIMENSIONS (MM)	Width - 87.5
CLASSIP RATINGIP20NPUT VOLTAGE230V 50HzSWITCH FUNCTIONIntermediateEARTH TERMINALYesCOAD/MAX. LOAD10AXTERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²VARRANTY15year(s)MANUFACTURED IN ACCORDANCE WITHBS EN 60669-1DRIGIN OF MANUFACTUREChinaDECLARATION OF CONFORMITY (HELD ON FILE)Yes	MINIMUM MOUNTING BOX DEPTH	16mm
P RATINGIP20NPUT VOLTAGE230V 50HzSWITCH FUNCTIONIntermediateEARTH TERMINALYesLOAD/MAX. LOAD10AXTERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²VARRANTY15year(s)MANUFACTURED IN ACCORDANCE WITHBS EN 60669-1DRIGIN OF MANUFACTUREChinaDECLARATION OF CONFORMITY (HELD ON FILE)Yes	CONSTRUCTION	Construction - Premium grade steel
NPUT VOLTAGE230V 50HzSWITCH FUNCTIONIntermediateEARTH TERMINALYesLOAD/MAX. LOAD10AXTERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²VARRANTY15year(s)MANUFACTURED IN ACCORDANCE WITHBS EN 60669-1DRIGIN OF MANUFACTUREChinaDECLARATION OF CONFORMITY (HELD ON FILE)Yes	CLASS	l
SWITCH FUNCTIONIntermediateEARTH TERMINALYesLOAD/MAX. LOAD10AXLOAD/MAX. LOAD10AXTERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²VARRANTY15year(s)MANUFACTURED IN ACCORDANCE WITHBS EN 60669-1DRIGIN OF MANUFACTUREChinaDECLARATION OF CONFORMITY (HELD ON FILE)Yes	IP RATING	IP20
EARTH TERMINALYes.OAD/MAX. LOAD10AX.OAD/MAX. LOAD2 x 1.0mm² or 2 x 1.5mm²TERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²VARRANTY15year(s)MANUFACTURED IN ACCORDANCE WITHBS EN 60669-1DRIGIN OF MANUFACTUREChinaDECLARATION OF CONFORMITY (HELD ON FILE)Yes	INPUT VOLTAGE	230V 50Hz
OAD/MAX. LOAD10AXTERMINAL CAPACITY2 x 1.0mm² or 2 x 1.5mm²VARRANTY15year(s)MANUFACTURED IN ACCORDANCE WITHBS EN 60669-1ORIGIN OF MANUFACTUREChinaDECLARATION OF CONFORMITY (HELD ON FILE)Yes	SWITCH FUNCTION	Intermediate
TERMINAL CAPACITY $2 \times 1.0 \text{mm}^2 \text{ or } 2 \times 1.5 \text{mm}^2$ VARRANTY15year(s)VANUFACTURED IN ACCORDANCE WITHBS EN 60669-1DRIGIN OF MANUFACTUREChinaDECLARATION OF CONFORMITY (HELD ON FILE)Yes	EARTH TERMINAL	Yes
WARRANTY 15year(s) MANUFACTURED IN ACCORDANCE WITH BS EN 60669-1 DRIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE) Yes	LOAD/MAX. LOAD	10AX
MANUFACTURED IN ACCORDANCE WITHBS EN 60669-1DRIGIN OF MANUFACTUREChinaDECLARATION OF CONFORMITY (HELD ON FILE)Yes	TERMINAL CAPACITY	2 x 1.0mm ² or 2 x 1.5mm ²
DRIGIN OF MANUFACTURE China DECLARATION OF CONFORMITY (HELD ON FILE) Yes	WARRANTY	15year(s)
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	MANUFACTURED IN ACCORDANCE WITH	BS EN 60669-1
	ORIGIN OF MANUFACTURE	China
AN 5055832016805	DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
505002510055	EAN	5055832916895

Date Created: 09/03/2022 12:57





ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification. ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.

