Knightsbridge


DATASHEET



CPL24CT

230V 24W CCT Adj Circular LED Panel- 290mm

www.mlaccessories.co.uk



MLA PART CODE	CPL24CT
DESCRIPTION	230V 24W CCT Adj Circular LED Panel- 290mm
NET WEIGHT (KG)	0.64
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 290 Projection - 15 Base Diameter - 246 Minimum Void - 50
CUT-OUT (MM)	Min./Max. Cut-out - 55 - 250
CONSTRUCTION	Construction - Polycarbonate
CLASS	ll
IP RATING	IP20
WATTAGE (W)	24
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	1940/2140/2100
LUMENS LIGHT SOURCE ONLY (LM)	3050
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	129.9
CIRCUIT WATTAGE (W)	23.5
ССТ	3000/4000/6000K
LIGHT COLOUR	ССТ
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.116
DISPLACEMENT FACTOR	>0.7



ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification. ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.



Knightsbridge

SVM	0.249
PST-LM	0.26
BEAM ANGLE (DEGREES)	120
LIFE SPAN (HRS)	
L70B50 LIFESPAN (HRS)	
DIMMABLE	No
IC RATED	Yes
OPERATING TEMPERATURE	-20~40°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	0.3
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832984184

Date Created: 09/03/2022 13:12





ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification. ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.

