Knightsbridge


DATASHEET



CPL6CT

230V 6W CCT Adj Circular LED Panel- 140mm

www.mlaccessories.co.uk



MLA PART CODE	CPL6CT
DESCRIPTION	230V 6W CCT Adj Circular LED Panel- 140mm
NET WEIGHT (KG)	0.18
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 140 Projection - 15 Base Diameter - 94 Minimum Void - 50
CUT-OUT (MM)	Min./Max. Cut-out - 55 - 100
CONSTRUCTION	Construction - Polycarbonate
CLASS	ll
IP RATING	IP20
WATTAGE (W)	6
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	400/430/410
LUMENS LIGHT SOURCE ONLY (LM)	655
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	120.2
CIRCUIT WATTAGE (W)	5.49
ССТ	3000/4000/6000K
LIGHT COLOUR	ССТ
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.046
DISPLACEMENT FACTOR	>0.5



ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification. ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.



Knightsbridge

SVM	0.049
PST-LM	0.04
BEAM ANGLE (DEGREES)	120
LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	30,000
DIMMABLE	No
IC RATED	Yes
OPERATING TEMPERATURE	-20~40°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	0.3
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832983910
Data Created: 00/02/2022 12:12	

Date Created: 09/03/2022 13:12





ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification. ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.

