Xnightsbridge


DATASHEET



230V 26W LED Emergency Batten 1525mm (5ft)

4000K

www.mlaccessories.co.uk



MLA PART CODE	T8BLED15EM1
DESCRIPTION	230V 26W LED Emergency Batten 1525mm (5ft) 4000K
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1525 Width - 60 Projection - 85
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP20
WATTAGE (W)	26
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	3000
LUMENS LIGHT SOURCE ONLY (LM)	3325
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	113
LUMENS EMERGENCY MODE (LM)	290
CIRCUIT WATTAGE (W)	24.65
ССТ	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.114
DISPLACEMENT FACTOR	>0.9
SVM	0.825





Xnightsbridge

PST-LM	0.038
BEAM ANGLE (DEGREES)	120
LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	50,000
DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched
OPERATING TEMPERATURE	-15~45°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	No
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 30W OUTPUT VOLTAGE - 34-49V OUTPUT CURRENT - 600mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 87.89 ISOLATION - SELV AMBIENT TEMPERATURE (Ta)15~45°C CASE TEMPERATURE (Tc) - 70°C
BATTERY INCLUDED	Yes
WARRANTY	5year(s)
WARRANTY INFORMATION	(excluding battery)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270803808
- · · · · · · · · · · · · · · · · · · ·	

Date Created: 09/03/2022 13:13





