Xnightsbridge


DATASHEET



SPIKE4BL

230V IP65 4W LED Wall/ Spike Light 3000K

www.mlaccessories.co.uk



MLA PART CODE	SPIKE4BL
DESCRIPTION	230V IP65 4W LED Wall/ Spike Light 3000K
NET WEIGHT (KG)	0.51
FINISH	Black
DIFFUSER	Clear
DIMENSIONS (MM)	Diameter - 60 Overall Height - 305 Spike Length - 173
CONSTRUCTION	Construction - Die-cast aluminium
CLASS	I
IP RATING	IP65
IK RATING	IK06
WATTAGE (W)	4
LAMP TECHNOLOGY	CoB LED
LAMP INCLUDED	Yes
LUMENS (LM)	355
LUMENS LIGHT SOURCE ONLY (LM)	460
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	136.79
CIRCUIT WATTAGE (W)	4.23
ССТ	3000K
LIGHT COLOUR	Warm White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.036
SVM	0.01





Xnightsbridge

PST-LM	0.03
BEAM ANGLE (DEGREES)	20
LIFE SPAN (HRS)	50,000
L70B50 LIFESPAN (HRS)	15,000
DIMMABLE	No
OPERATING TEMPERATURE	25°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	3
CABLE TYPE	3 x 1.0mm ² H05RN-F
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 3.5W OUTPUT VOLTAGE - 3-10V OUTPUT CURRENT - 350mA EFFICIENCY FULL LOAD - 80 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - 45°C CASE TEMPERATURE (Tc) - 75°C
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270805642
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes

Date Created: 09/03/2022 13:14





