Xnightsbridge

DATASHEET




LDGL9

230V IP65 9W LED Stainless Steel Recessed Ground Light 3000K

ereance Eight erean

www.mlaccessories.co.uk



MLA PART CODE	LDGL9
DESCRIPTION	230V IP65 9W LED Stainless Steel Recessed Ground Light 3000K
NET WEIGHT (KG)	1.17
FINISH	Stainless Steel
DIFFUSER	Clear
DIMENSIONS (MM)	Diameter - 160 Projection - 4 Recessed Depth - 88
CUT-OUT (MM)	Cut-out Diameter - 138 Cut-out with Sleeve - 144
CONSTRUCTION	Construction - 304 Stainless steel
CLASS	I
IP RATING	IP65
WATTAGE (W)	9
LAMP TECHNOLOGY	CoB LED
LAMP INCLUDED	Yes
LUMENS (LM)	610
LUMENS LIGHT SOURCE ONLY (LM)	655
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	77.61
CIRCUIT WATTAGE (W)	8.5
ССТ	3000К
LIGHT COLOUR	Warm White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.067





Xnightsbridge

DISPLACEMENT FACTOR	>0.9
SVM	0.015
PST-LM	0.22
BEAM ANGLE (DEGREES)	100
LIFE SPAN (HRS)	25,000
L70B50 LIFESPAN (HRS)	50,000
LED COMPATIBLE	Yes
DIMMABLE	No
MAX. WEIGHT LOADING	800kg at 5mph
OPERATING TEMPERATURE	-25~35°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	2
CABLE TYPE	3-core 1.00mm ² H05RN-F
WARRANTY	2year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270800418

Date Created: 09/03/2022 13:19





