

**63A 400V Interlocked Switched  
RCD Skt 3P+N+E IP65**

Features and Benefits

Safety:

The Interlocked sockets are equipped with rear panel isolator switches AC3-AC23A which guarantees;

- Load break disconnect at nominal current
- Insulation in OFF position, thanks to safe distances between contacts
- 10,000 switching cycles at full load
- Prevention - all control gear windows are fitted with locking device to avoid unauthorized access.

All interlocked sockets can be locked both at position 0 and 1

Interlocked sockets are equipped with an integral switch ensuring safe electrical disconnection and isolation.

In order to prevent disconnection of the plug and socket coupling under load, it is not possible to turn the integral isolator switch to the 'on' position until a mating plug has been fully inserted. The plug cannot then be withdrawn until the isolator has been selected to the 'off' position.

It is possible to padlock the isolation switch in both the on and off positions.

Design Characteristics

- Design Characteristics
- 63A 400VAC 3P+N+E switched and mechanically interlocked socket outlet in compliance with IE-C60309-1-2, IEC 60529, IEC60947-3
- Thermoplastic construction suitable for outdoor environment.
- Impact resistance >>IK08
- IP65 ingress protection rating
- Featuring integral 63A 2P 30mA residual current device (BSEN61008 type AC) located behind a transparent hinged access window
- Dimensions (As seen on the diagram);

395MM - 121.5mm / 80.5 - A = Max 80mm - 146mm

