

Telco

Technical Data Sheet

Product Type:SpotlightsProduct Code:T440838-WH/DL/830Product Code:WhiteBody Colour:Surface MountedMounting:Surface Surface Mounting PlatePendant Stem Length(mm)-Vertical Mount:InteriorSize(mm)87 × 60 × 120Cut Out(mm):-Recessed Depth(mm):-Vertical Tit(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Life(Hours):50000 hoursLume Output(Im):3000k Warm WhiteColour Temperature(k):300k Warm WhiteColur Temperature(k):0.05Power Factor:-Luminaire Efficacy(Im/W):1.12WClass:Gaits 1Gear:Built InEAN Code:-Immainity:Leading/Trailing Edge DimmableFating:120Power Factor:-Immainity:-Immainity:-Immainity:-Immainity:-Immainity:-Power Factor:-Immainity:-Immainity:-Immainity:-Immainity:-Immainity:-Immainity:-Immainity:-Immainity:-Immainity:-Immainity:-Immainity:-Immainity:-Immainit	Range Name:	Lumapar LED
Product Code::T440838-WH/DL/830Body Colour::WhiteMounting:Surface MountedTrack Adaptor:Surface - Surface Mounting PlatePendant Stem Length(mm):-Vertical Mount:-Size(mm)87 × 60 × 120Cut Out(mm):-Recessed Depth(mm):90°Vertical Tit(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Sase:-Lamp Life(Hours):50000 hoursLumen Output(Im):800ImColour Temperature(k):300k Warm WhiteCRI(Ra):85Beam Angle(°):38°Vottag(V):200VACTotal System Power(M):1.1.2WLumine Efficacy(Im/W):7.1 In/WClass:Class:Gear:Built InExarceSPower Factor:-Jimmbility:Leading/Trailing Edge DimmableEmergency:-Pirating:1/20Weight(kg):0.3kgHousing Material:AuminiumMaterial Finish:Power Coated	Product Type:	Spotlights
Body Colour:WhiteMounting:Surface MountedMounting:Surface - Surface Mounting PlatePendant Stem Length(mm):-Vertical Mount:-Environment:InteriorSize(mm)87 x 60 x 120Cut Out(mm):-Recessed Depth(mm):-Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Colour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):11.2WLamp Cutrent(A):0.05Power Factor:-Luminaire Efficacy(Im/W):71 Im/WClass:Class 1Gear:Built InEAN Code:-I' Pating:I' P20Weight(kg):0.3kgHousing Material:AluminiumMaterial Finish:Power Coated	Product Code:	
Mounting:Surface MountedTrack Adaptor:Surface - Surface Mounting PlatePendant Stem Length(mm):-Vertical Mount:NateriorSize(mm)87 × 60 × 120Cut Out(mm):-Recessed Depth(mm):90°Vertical Tilt(°):90°Uotical Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLumen Output(Im):800InColour Temperature(k):3000k Warm WhiteCRI(Ra):83°Power Factor:1.2WLuminaire Efficacy(Im/W):1.12WClass:Class 1Gear:Built InEAN Code:-Immability:Leading/Trailing Edge DimmableEmergency:-IP Rating:N20Weight(kg):0.3kgHousing Material:Nower Coated		
Track Adaptor:Surface - Surface Mounting PlatePendant Stem Length(mm):-Environment:InteriorSize(mm)87 × 60 × 120Cut Out(mm):-Recessed Depth(mm):0°Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Colour Temperature(k):3000 hoursLume Output(Im):800ImCraft(Ra):85°Beam Angle(°):300k Warm WhiteCraft(Ra):230VACTotal System Power(W):11.2WLuminaire Efficacy(Im/W):71 Im/WClass:Class 1Gear:Built InEAN Code:-Pomer Factor:61FAN Code:-Pinmability:120Weight(kg):0.3kgHousing Material:AluminiumHousing Material:Power Coated	Body Colour:	White
Pendant Stem Length(mm);·Vertical Mount:·Environment:NteriorSize(mm)·Cut Out(mm):·Recessed Depth(mm):·Vertical Tilt(°):90°Horizontal Rotation(°):JS5°Light Source:LEDLamp Type:CREE LEDLamp Type:S000 hoursLamp Life(Hours):S000 hoursLume Output(Im):800ImColour Temperature(k):3000k Warm WhitePower Factor:0.05Lamp Current(A):0.05Lamp Current(A):0.112WLamp Current(A):Class 1Cass:Class 1Cass:SFactor:Painting Edige DimmableEarierNontract Painting Edige DimmableFarting:Notract Painting Edige DimmableFarting:SCass:SFarting:Painting Edige DimmableFarting:Painting Edige DimmableFarting:SFarting:SFarting:Painting Edige DimmableFarting:Painting Edige DimmableFarting:P	Mounting:	Surface Mounted
Vertical Mount:-Environment:InteriorSize(mm)87 × 60 × 120Cut Out(mm):-Recessed Depth(mm):90°Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Type:000 hoursLumen Output(Im):800ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85°Beam Angle(°):300k Warm WhiteCtal System Power(W):11.2WLuminaire Efficacy(Im/W):71 Im/WClass:Calss 1Gear:Built InEAN Code:-Dimmability:Leading/Trailing Edge DimmableEmergency:-IP Rating:0.3kgHousing Material:0.3kgHousing Material:0.3kurnikaKetrial Finish:Power Coated	Track Adaptor:	Surface - Surface Mounting Plate
Environment:InteriorSize(mm)87 x 60 x 120Cut Out(mm):-Recessed Depth(mm):-Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Lumen Output(Im):800ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85°Beam Angle(°):3000k Warm WhiteCtal System Power(W):11.2WLuminaire Efficacy(Im/W):71 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:Leading/Trailing Edge DimmableEmergency:-IP Rating:0.3kgHousing Material:0.3kgHousing Material:Power Coated	Pendant Stem Length(mm):	-
Size(mm)87 × 60 × 120Cut Out(mm):-Recessed Depth(mm):-Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Dase:-Lumen Output(Im):8001mColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):230VACTotal System Power(W):11.2WLuminaire Efficacy(Im/W):71 Im/WClass:Class 1Gear:Built InEAN Code:-Immability:Leading/Trailing Edge DimmableEmergency:-IP Rating:0.3kgHousing Material:AluminiumMeterial Finish:Power Coated	Vertical Mount:	-
Cut Out(mm):-Recessed Depth(mm):-Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Lamp Life(Hours):50000 hoursLumen Output(Im):800ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):230VACTotal System Power(W):11.2WLuminaire Efficacy(Im/W):71 Im/WClass:Class 1Gear:Built InEAN Code:-Imability:Leading/Trailing Edge DimmableEmergency:-IP Rating:N3kgHousing Material:0.3kgHousing Material:Power Coated	Environment:	Interior
Recessed Depth(mm):-Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Lamp Life(Hours):50000 hoursLumen Output(Im):800ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):230VACTotal System Power(W):11.2WLuminaire Efficacy(Im/W):71 Im/WClass:Cass 1Gear:Built InEAN Code:-Immability:Leading/Trailing Edge DimmableFmergency:-IP Rating:IP20Weight(kg):0.3kgHousing Material:AluminiumPower Coated-	Size(mm)	87 x 60 x 120
Vertical Tilt(°):90°Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Lamp Life(Hours):50000 hoursLumen Output(Im):800ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):230VACTotal System Power(W):11.2WLamp Current(A):0.05Power Factor:-Class:Class 1Gear:Built InEAN Code:-Dimmability:Leading/Trailing Edge DimmableEmergency:-IP Rating:1920Weight(kg):0.3kgHousing Material:AluminiumMeterial Finish:Power Coated	Cut Out(mm):	-
Horizontal Rotation(°):355°Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Lamp Life(Hours):S000 hoursLumen Output(Im):800ImColour Temperature(k):300k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):230VACTotal System Power(W):11.2WLamp Current(A):0.05Power Factor:-Class:Gass 1Gear:Built InEAN Code:-Dimmability:Leading/Trailing Edge DimmableEmergency:-IP Rating:IP20Meight(kg):0.3kgHousing Material:Power Coated	Recessed Depth(mm):	-
Light Source:LEDLamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Lamp Life(Hours):S000 hoursLumen Output(Im):800ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):230VACTotal System Power(W):11.2WLamp Current(A):0.05Power Factor:-Luminaire Efficacy(Im/W):71 Im/WClass:Class 1Gear:Built InEAN Code:-Immability:Leading/Trailing Edge DimmableEmergency:0.3kgHousing Material:0.3kgMaterial Finish:Power Coated	Vertical Tilt(°):	90°
Lamp Type:CREE LEDLamp Included:In BuiltLamp Base:-Lamp Life(Hours):50000 hoursLumen Output(Im):800ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):230VACTotal System Power(W):11.2WLamp Current(A):0.05Power Factor:-Class:Class 1Gear:Built InEAN Code:-Dimmability:Leading/Trailing Edge DimmableEmergency:-IP Rating:IP20Housing Material:AluminiumMaterial Finish:Power Coated	Horizontal Rotation(°):	355°
Lamp Included:In BuiltLamp Base:-Lamp Life(Hours):50000 hoursLumen Output(Im):800ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):230VACTotal System Power(W):11.2WLamp Current(A):0.05Power Factor:-Luminaire Efficacy(Im/W):71 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:Leading/Trailing Edge DimmableEmergency:-IP Rating:IP20Weight(kg):0.3kgHousing Material:AluminiumPower Coated-	Light Source:	LED
Lamp Base:-Lamp Life(Hours):50000 hoursLumen Output(Im):800ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):230VACTotal System Power(W):11.2WLamp Current(A):0.05Power Factor:-Luminaire Efficacy(Im/W):71 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:Leading/Trailing Edge DimmableEmergency:-IP20Weight(kg):MuiniumAluminiumHousing Material:AluminiumMaterial Finish:Power Coated	Lamp Type:	CREE LED
Lamp Life(Hours):50000 hoursLumen Output(Im):800ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):230VACTotal System Power(W):11.2WLamp Current(A):0.05Power Factor:-Luminaire Efficacy(Im/W):71 Im/WGear:Built InEAN Code:-Dimmability:Leading/Trailing Edge DimmableEmergency:-IP20Weight(kg):Muising Material:AluminiumMaterial Finish:Powder Coated	Lamp Included:	In Built
Lumen Output(Im):800ImColour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):230VACTotal System Power(W):11.2WLamp Current(A):0.05Power Factor:-Luminaire Efficacy(Im/W):71 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:Leading/Trailing Edge DimmableEmergency:0.3kgHousing Material:AluminiumMaterial Finish:Powder Coated	Lamp Base:	-
Colour Temperature(k):3000k Warm WhiteCRI(Ra):85Beam Angle(°):38°Voltage(V):230VACTotal System Power(W):11.2WLamp Current(A):0.05Power Factor:-Luminaire Efficacy(Im/W):71 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:Leading/Trailing Edge DimmableEmergency:-IP Rating:0.3kgHousing Material:AluminiumMaterial Finish:Powder Coated	Lamp Life(Hours):	50000 hours
CRI(Ra):85Beam Angle(°):38°Voltage(V):230VACTotal System Power(W):11.2WLamp Current(A):0.05Power Factor:71 lm/WClass:Class 1Gear:Built InEAN Code:-Dimmability:Leading/Trailing Edge DimmableEmergency:0.3kgHousing Material:MuminiumMaterial Finish:Power Coated	Lumen Output(Im):	800lm
Beam Angle(°):38°Voltage(V):230VACTotal System Power(W):11.2WLamp Current(A):0.05Power Factor:-Luminaire Efficacy(Im/W):71 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:Leading/Trailing Edge DimmableEmergency:0.3kgHousing Material:AluminiumMaterial Finish:Powder Coated	Colour Temperature(k):	3000k Warm White
Voltage(V):230VACTotal System Power(W):11.2WLamp Current(A):0.05Power Factor:-Luminaire Efficacy(Im/W):71 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:Leading/Trailing Edge DimmableEmergency:-IP Rating:IP20Weight(kg):O.3kgHousing Material:AluminiumMaterial Finish:Powder Coated	CRI(Ra):	85
Total System Power(W):11.2WLamp Current(A):0.05Power Factor:-Luminaire Efficacy(Im/W):71 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:Leading/Trailing Edge DimmableEmergency:-IP Rating:IP20Weight(kg):0.3kgHousing Material:AluminiumMaterial Finish:Powder Coated	Beam Angle(°):	38°
Lamp Current(A):0.05Power Factor:-Luminaire Efficacy(Im/W):71 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:Leading/Trailing Edge DimmableEmergency:-IP Rating:IP20Weight(kg):0.3kgHousing Material:AluminiumMaterial Finish:Powder Coated	Voltage(V):	230VAC
Power Factor:-Luminaire Efficacy(Im/W):71 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:Leading/Trailing Edge DimmableEmergency:-IP Rating:IP20Weight(kg):0.3kgHousing Material:AluminiumMaterial Finish:Powder Coated	Total System Power(W):	11.2W
Luminaire Efficacy(Im/W):71 Im/WClass:Class 1Gear:Built InEAN Code:-Dimmability:Leading/Trailing Edge DimmableEmergency:-IP Rating:IP20Weight(kg):0.3kgHousing Material:AluminiumMaterial Finish:Powder Coated	Lamp Current(A):	0.05
Class:Class 1Gear:Built InEAN Code:-Dimmability:Leading/Trailing Edge DimmableEmergency:-IP Rating:IP20Weight(kg):0.3kgHousing Material:AluminiumMeterial Finish:Powder Coated	Power Factor:	-
Gear:Built InEAN Code:-Dimmability:Leading/Trailing Edge DimmableEmergency:-IP Rating:IP20Weight(kg):0.3kgHousing Material:AluminiumMaterial Finish:Powder Coated	Luminaire Efficacy(Im/W):	71 lm/W
EAN Code:-Dimmability:Leading/Trailing Edge DimmableEmergency:-IP Rating:IP20Weight(kg):0.3kgHousing Material:AluminiumMaterial Finish:Powder Coated	Class:	Class 1
Dimmability:Leading/Trailing Edge DimmableEmergency:-IP Rating:IP20Weight(kg):0.3kgHousing Material:AluminiumMaterial Finish:Powder Coated	Gear:	Built In
Emergency:-IP Rating:IP20Weight(kg):0.3kgHousing Material:AluminiumMaterial Finish:Powder Coated	EAN Code:	-
IP Rating:IP20Weight(kg):0.3kgHousing Material:AluminiumMaterial Finish:Powder Coated	Dimmability:	Leading/Trailing Edge Dimmable
Weight(kg):0.3kgHousing Material:AluminiumMaterial Finish:Powder Coated	Emergency:	-
Housing Material:AluminiumMaterial Finish:Powder Coated	IP Rating:	IP20
Material Finish: Powder Coated		0.3kg
	Housing Material:	Aluminium
Guarantee: 5 Year Guarantee	Material Finish:	Powder Coated
	Guarantee:	5 Year Guarantee







Images, line drawings and measurements illustrated may, in some cases be approximate and for guidance only. Colour finishes will be maintained as accurately as possible but matching cannot be guaranteed. Technical specifications subject to change without prior notice.