

Technical Specification

Product Code: CHOICE PR3n

Description: Three channel programmer, three independent time controlled

channels. 2 individual heating zones and separate hot water control.





General Information

Dimensions 140mm x 87mm x 37mm

Display Backlit LCD

Clock 12 hour am/pm, 1 minute resolution,

accuracy +/- 1.5 sec/day

Heating System Pumped or Gravity

Power

Operating Voltage 100 ~ 240 VAC

Battery Type Lithium Cell CR2032

IEC Protection Class II

Construction

Material Thermoplastics, Flame Retardant

Fixing Surface Only
Wiring Fixed wiring only

Outputs

Total Switch Rating 230V AC, 2(1)A (per channel)

Contact Type 1B, Micro-Disconnection

Programming

Programming Schedule 24 Hour, 5/2 Day and 7 Day Programma-

ble

Available Operations 2 or 3 ON/OFF Periods

Modes Available On, Off, Auto, All Day

Pre-Programmed Schedule Yes

Summer/Winter Time Yes; Automatic

Change

Holiday Mode Yes

Boosts

Selectable Durations 1,2 or 3 Hour Boost

Environment

Ingress ProtectionIP30Operating Temperature0°C to 40°C

Features

24 hour, 5/2 day and 7 day selectable 2 or 3 ON/OFF periods selectable

1, 2 or 3 hour boost

Advance to next programmed event Automatic Summer/Winter time change

Standard wall plate - simple plug in and replace

Pumped or gravity system selectable





