


SFX/ISP2-LSF-GRY

ISP2 2pr 22AWG Individual Foil Screen 600V Grey LSF (8723) CPR:Eca



<b>Cable Construction</b>	2 Pairs
Conductor	Tinned Copper
Conductor Diameter (mm)	0.24 ±0.008 x 7(0.33mm <sup>2</sup> )
Stranded Diameter (mm)	0.64
<b>Insulation</b>	FPE
Insulation Thickness (mm)	0.24
Insulation Diameter (mm)	1.20 ±0.10
Insulation Colour(s)	Red,Black;Green,White
Al-PET Shield	≥115% (On each pair)
<b>Drain Wire</b>	
Drain Wire Conductor	Tinned Copper
Drain Wire Conductor Diameter (mm)	0.19 ±0.008 x 7
<b>Nylon Rip-Cord</b>	White 210D
<b>Jacket</b>	LSF
Jacket Thickness (mm)	0.450
Overall Diameter (mm)	4.10 ±0.20
Jacket Colour	Grey RAL 7042
Sheath Printing	ISP2 2x2x22AWG 600V Individually Screened LSF RoHS2 (PO) (m)
Reaction to Fire	Eca
<b>Electrical Characteristics</b>	
Max Conductor DC resistance @ 20°C	<50Ω/km
Rated Temperature (°C)	-20°C to 80°C
Rated Voltage (V)	600V
Insulation Resistance @20°C	>200MΩ/km
Standards	CE2014/30/EU, RoHS2 2011/65/EU, LVD 2014/35/EU
Application	Audio, control and Instrumentation.