


SFX/6C-TY3-PVC-WHT

6 Core TCCA Type 3 Alarm Cable White PVC CPR:Eca to BS4737-3.30:2015



<b>Cable Construction</b>	6 Cores
Conductor	Tinned Copper Clad Aluminium
Conductor Diameter (mm)	0.20 ±0.008 x 7
Stranded Diameter (mm)	0.22
<b>Insulation</b>	PVC
Insulation Thickness (mm)	0.21
Insulation Diameter (mm)	1.00 ±0.100
Insulation Colour(s)	Red,Black,Blue, Yellow,Green,White
<b>Nylon Rip-Cord</b>	Yellow 210D
<b>Jacket</b>	PVC
Jacket Thickness (mm)	0.50
Overall Diameter (mm)	4.00 ±0.200
Jacket Colour	White RAL 9003
Sheath Printing	(m)
Reaction to Fire	Eca
<b>Electrical Characteristics</b>	
Max Conductor DC resistance @ 20°C	155Ω/km
Rated Temperature (°C)	-20°C to 80°C
Rated Voltage (V)	30V
Insulation Resistance @20°C	>200 MΩ/km
Compliance and Standards	BS4737-3.30:2015,RoHS2 2011/65/EU
Application	For the interconnection of intruder alarm installations.