

Data Sheet

Product Code: XDYT71VS.PD

Product Description: 2-Gang (10A Intermediate Switch + 10A 1- or

2-Way Toggle Switch)

Range: Screwless

Finish: Primed

Product Category: Intermediate Toggle Switch

Insert/Knob Colour: Brass Toggle

Barcode: 5021575998214

Dimensions: 86x86x36mm

Faceplate Depth: 4mm

Net Weight: 126g

Gross Weight: 128g

Fixing Centres: 60.3mm

Depth from Mounting Face: 17.4mm

Recommended Back Box Depth: 25mm

Operating Voltage: 230v 50Hz

Maximum Load Rating: 10A

Maximum Current Rating: 10A

Terminal (Live) Diameter: 3.3 mm; Capacity: $3 \times 1.5 mm^2$

Terminal (Earth) Diameter: 3.3mm; Capacity: 3 x 1.5mm²

Intended Applications: Indoor Use Only. Domestic lighting circuits.

Safety Advice: Product Must Be Earthed.

Applicable Safety Standard: BS EN 60669-1

.. ,

Commodity Code: 85365007



Product Features

2 x intermediate (3-way) switches

② Suitable for controlling both mains and low voltage lighting

Intermediate switch enables 3-way switching

❷ Sleek, low-profile screwless faceplate

❷ For helpful tips on painting the Varilight Primed range, featuring different paints and methods, see our Varilight Primed - Best Practices article.



10 YEAR GUARANTEE



All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to identify latest version.

Date of Issue: 22nd April 2022 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.