Radiant Heaters

- Economical and easy to install
- Silent in operation
- No yearly maintenance cost
- Instant heat from switch on
- Precision heating directed where needed





Profile

The Vent-Axia radiant heating product range gives the flexibility to deal with large and small unheated spaces which would be uneconomical to heat using traditional space heating.

Areas such as bars, restaurants, terraces, delivery areas, warehouses and churches are some examples where the radiant heating products will provide an economical heating solution.

Radiant heat and its advantages


The heat felt from the sun is called radiant heat and is part of the electromagnetic spectrum called infrared. Ultra violet and visible light also belong to the same family.

Visible light is the easiest part of this spectrum to understand, light travels in a straight line from the source, is unaffected by air and is invisible until it hits a surface. Shadows are a good example of this and are the absence of light.

Infrared rays behave in the same way, they cannot be seen but can be felt as warmth. A good example of this is the effect created when you move from the shade into the sun, although the temperature is the same, the perceived temperature when in direct sunlight is much higher. This phenomenon makes sunbathing possible during winter holidays. There are three categories of infrared; short wave (IR A), medium wave (IR B) and long wave (IR C), the shorter the wave length the easier it travels through the air.

The advantage when using short wave infrared heating is that the rays cut through the air and are not affected by air movement and only transmits its energy when it collides with a solid object. The rays also travel in a straight line so can be directed where you need it, ideal in locations which feature high ceilings, have high air change rates or are outside.

Convection Heating and Radiant Heating Comparison



Wave Infrared comparison

	Short Wave Infrared	Medium Wave Infrared	Long Wave Infrared
Typical source	IR Halogen Lamp	Quartz Heat Source	Resistance
Materials	Tungsten Filament welded in a quartz tube	Filament in compound of Fe-Cr-Al in a quartz tube	Filament in compound of Fe-Cr-Al in a steel tube
Radiant efficiency	92%	60%	40%
Switch on/off times	1 second	30 second	5 minutes




Models



Model Sunburst 2kW Stock Ref SUNB2000BL-VA


Dimensions (mm)



	TROIN		JIDL	
Stock Ref	Α	В	С	D
SUNB2000BL-VA	190	460	113	107



Model Sunburst 3kW Stock Ref SUNB3000BL-VA



Technical Details

Stock RefModelkgVoltage ratingspectrumAccessoriesWAmpsSUNB2000BL-VASunburst 2kW2.6220-240V 50HzIR-AWall bracket20009	range m²						Weight		
SUNB2000BL-VA Sunburst 2kW 2.6 220-240V 50Hz IR-A Wall bracket 2000 9	runge III	Amps	W	Accessories	spectrum	Voltage rating	kg	Model	Stock Ref
	10-12	9	2000	Wall bracket	IR-A	220-240V 50Hz	2.6	Sunburst 2kW	SUNB2000BL-VA
SUNB3000BL-VA Sunburst 3kW 4.6 220-240V 50Hz IR-A Wall bracket 3000 14	18-36	14	3000	Wall bracket	IR-A	220-240V 50Hz	4.6	Sunburst 3kW	SUNB3000BL-VA